

LAYING DOWN A WHOLE NEW
STANDARD IN TOPDRESSING

CONTROL AND PRECISION.



PRESENTING THE **WIDESPIN™ 1550.**

Topdressing is no longer a guessing game. With the new WideSpin™ 1550, you're in complete control of your topdressing program. You'll get the application rates you want, when you need them...without leaving the seat.

- ▶ **NEW PATENT PENDING** controller allows you to calculate your rates while also giving you a wider range of rates to choose from. Lock in your favorites using the controller's four presets.
- ▶ **NEW HYDRAULIC SYSTEM AND SPINNER DESIGN** makes the patented WideSpin technology even more versatile while delivering a consistent, even spread. Go from a new, superlight application to heavy, and everything in between.
- ▶ **NEW HOPPER** has 20% greater capacity and the widest opening in the industry—you'll refill faster and spill a lot less when you do.

Whether you use a tow-behind or truck-mount, see why the WideSpin 1550 is the new standard in topdressing. Give us a call and we'll arrange for a head-to-head comparison with your current topdresser.



CALL 1-800-679-8201 for a FREE on-site demonstration, or **VISIT www.TURFCO.com**



Specifications

	TOW-BEHIND		TRUCK-MOUNTED
			TORO, JOHN DEERE & JACOBSEN
Model	ENGINE POWERED 1550 Electronic Control (#85820) 1550 Manual Control (#85821)	HYDRAULIC POWERED 1550 Electronic Control (#85824) 1550 Manual Control (#85825)	HYDRAULIC POWERED 1550 Electronic Control (#85822) 1550 Manual Control (#85823)
Engine	13 HP Briggs and Stratton Vanguard		n/a
Operator Control	Electric: 3-position switch; 4 programmable presets; onboard rate calculator; instantaneous belt and spinner speed control Manual: Standard 3-position switch with manual control	Electric: 3-position switch; 4 programmable presets; onboard rate calculator; instantaneous belt and spinner speed control Manual: Standard 3-position switch with manual control	Electric: 3-position switch; 4 programmable presets; onboard rate calculator; instantaneous belt and spinner speed control Manual: Standard 3-position switch with manual control
Empty Weight	1,324 lbs (601 Kg)	1,021 lbs (463 Kg)	710 lbs without mounting kit (322 Kg)
Hopper Capacity	21 ft ³ (0.59 m ³) struck level; 25 ft ³ (0.71 m ³) heaped		
Hopper Size	69.5" x 59.1" (1.77 x 1.50 m) at the top		
Spreading Width	9' up to 40' (2.5 up to 12 m)		
Spread Application	0.45 ft ³ per 1,000 ft ³ up to 12 ft ³ per 1,000 ft ³ using patented WideSpin Technology		
Topdressing Speed	Up to 8 MPH (12.8 Km/h)	Up to 8 MPH (12.8 Km/h)	Up to 5 MPH (8 Km/h)
Transport Speed	Up to 8 MPH (12.8 Km/h)	Up to 8 MPH (12.8 Km/h)	Up to 8 MPH (12.8 Km/h)
Conveyor Belt	18" (0.46 m) wide pebble surface composition with heavy duty polyester cord		
Metering Gate	Manually operated with Light Spread/Heavy Spread Calibrations		
Drive	Engine Powered Hydraulics	Tow Vehicle Powered Hydraulics	Truck Powered Hydraulics
Wheels	4 Ply 26.5 x 14.00 x 12 Turf	4 Ply 26.5 x 14.00 x 12 Turf	n/a
Warranty	3 years		
Options	n/a	<ul style="list-style-type: none"> Cushman Truck Carriage Mounting Kit for WideSpin 1550 (#85824 or #85825) to a Carriage (#86184), includes hoses & wiring for Cushman Truck (#86190) Toro, John Deere or Jacobsen Truck Carriage Mounting Kit for WideSpin 1550 (#85824 or #85825) to a Carriage (#86184), includes hoses & wiring for Toro, John Deere or Jacobsen Trucks (#86191) Tractor Carriage Mounting Kit for WideSpin 1550 (#85824 or #85825) to a Carriage (#86184), includes hoses & wiring for tractors (#86192) 	<ul style="list-style-type: none"> Mounting Kit to Toro Workman HDX and 2002 or later Toro Workman Trucks equipped with the Toro High Flow Hydraulic Kit (#86188) Mounting Kit to John Deere ProGator Truck equipped with John Deere Hydraulic Auxiliary Kit (#86189) Mounting Kit for Jacobsen XD Truck (#86502) Trench-filler attachment (#86150), Cross Conveyor Attachment (#86181) Storage Stand (#86197)