

AR530

ARTICULATED CONTOUR ROTARY MOWER



- **TRUEDECK™ HEAVY-DUTY CONTOURING**
- **SUPERIOR AFTER-CUT APPEARANCE**
- **QUICK AND EASY DECK ADJUSTMENT**
- **TRUSTWORTHY KUBOTA® ENGINE**

Redesigned from the ground up, the AR530 contour rotary mower is built to give you the best.

Designed with TRUEDECK™ heavy-duty contouring decks, with best in class clippings distribution and superior after-cut quality, it climbs hills and contours smoothly, eliminating the risk of scalping.

The AR530 offers quick and easy deck adjustments and a trustworthy Kubota® engine you can rely on.

CUT WIDTH 90" (2.3M)	CUT HEIGHT 0.75" - 4.5" (19MM - 114MM) 0.25" (6MM) INCREMENTS	CUTTING CAPACITY UP TO 5.66 AC (2.29HA) / HR AT 7MPH (11.26KM/H)
FUEL CAPACITY 17 GAL (64.2L)	MOWER ENGINE KUBOTA® 50.2HP (37.4KW) DIESEL	TRANSPORT SPEED 12 MPH (19.3KPH)



SINCERELY

Jake

For information and support:
www.jacobsen.com / +44 (0) 1473 270 000



Engine horsepower may vary due to conditions of specific use. Product available in selected countries.
 NOTE: Specifications, while correct at time of printing, may change without notice.
 © 2021 Textron Specialized Vehicles Inc.

AR530

ARTICULATED CONTOUR ROTARY MOWER



DECKS & CUTTING UNITS

NUMBER AND SIZE	5 x TRUEDECK™ 23" (58.4cm) rotary cutting units. Equipped for rear-discharge chute and smooth rear roller. Mulching baffle, non-stripping rear roller and rear roller scrapers available
BLADE MATERIAL	5 x 22.4" (56.8cm) heat treated alloy combo blades
DECK LIFT & LOWER	Hand operated, joystick controlled hydraulic lift system
WEIGHT TRANSFER	Adjustable hydraulic weight transfer – automatic electronic activation at operator controls with mow switch. Selectable through control console
DECK CONSTRUCTION	10-gauge, heavy duty modular deck construction

TRACTION, BRAKES & SPEED

TRACTION DRIVE	SureTrac II™ AWD, a unique parallel hydrostatic system, servo-controlled variable displacement hydro; four high-torque wheel motors; 2WD transport and reverse
DECK DRIVE	Fixed displacement, self-lubricating with 1" (2.54cm) diameter shaft; double sealed bearings
HYDRAULIC SYSTEM	10 gal. (37.9L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter, 40 gpm. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic through traction system
PARKING BRAKES	No-Maintenance, Integrated Wet Parking Brake
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	7mph (11.3km/h)
REVERSE SPEED	8.7mph (14km/h)

WEIGHTS & DIMENSIONS

WEIGHT	3451lb. (1565kg) full fluids
LENGTH	137.5" (3.49m)
OVERALL HEIGHT (ROPS UP)	91.6" (232.6cm)
WHEELBASE	63" (1.6m)
TRANSPORT WIDTH	88.6" (2.25m)
WORKING WIDTH	95.3" (2.42m)

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

■ 692771 Blade 23.14 Hi-lift	■ 677092 Kit - mulching, 23"	■ 698270 Roller - service 76 x 567 grooved polymer
■ 692774 Blade 23.14 combo	■ 677261 Kit - quick release pin, 7 gang	■ 698272 Roller - service 76 x 567 solid polymer
■ 692775 Blade 23.14 mulch	■ 686406 Kit - hood latch lock	■ 4394939 Acc, cargo net
■ 68127 Canopy kit	■ 687204 Kit - ROPS bracket	■ 10002064 Kit - 23" grooved roller scraper
■ 677080 Kit - quick release pin, 5 gang	■ 689563 Kit - 23" cable scraper	■ 10013137 Kit - deck bumper 23"