



**BAUMAN**  
MANUFACTURING



**DROP SPREADERS**

**SALT IT. SAND IT. SPREAD IT.**

# Models

Bauman drop spreaders prevent waste and property damage with the most accurate de-icing dispensing equipment on the market. Backed by a tradition of quality for over 40 years and with 7 models to choose from, Bauman has the right solution for you.

**220**

Manual Push Style  
Capacity: 2 cubic feet  
Spreading Width: 20 inches



**440**

Electric or Hydraulic Drive  
Capacity: 4 cubic feet  
Spreading Width: 40 inches



**640**

Hydraulic or PTO Drive  
Capacity: 6.5 cubic feet  
Spreading Width: 40 inches  
Various Mounting Brackets Available



**1140**

Hydraulic or PTO Drive  
Capacity: 11 cubic feet (expandable to 16 cubic feet with optional extensions)  
Spreading Width: 40 inches



**1040SI**

Electric Drive  
Capacity: 10 cubic feet  
Spreading Width: 40 inches  
Designed to Work with Many Utility Vehicles



**1040B/  
1560B**

Hydraulic Drive  
Capacity: 10/15 cubic feet  
Spread Width: 40 inches/60 inches  
Various Mounting Brackets Available



\*1040B shown



# Features

## AGITATOR BAR

The agitator bar rotates in the hopper to reduce salt or sand from bridging. The bar ensures material passes through to the drum and then to the ground for an even application.



## FINGER BAR

A unique polymer finger bar has a flexible memory in very cold weather to retain its shape. This gives all Bauman drop sanders the even cross hatch pattern when the material is dropped.



## SALT DRUM

The rotating drums allow placement of de-icing material such as coarse rock salt where needed to give controlled delivery of material.



## SAND DRUM

The rotating drums allow placement of de-icing material such as sand and environmentally smart de-icing products where needed to give controlled delivery of material.



## ELECTRIC MOTOR

12 volt ¼ hp DC electric motor and reducer drives the 440E and 1040SI drop sanders. The epoxy paint protects units from salt brine and a slushy environment for long life.



## FLOW CONTROL

Flow control is included on all hydraulic units. It controls the hydraulic oil flow from the tractor to the motor that controls the speed of the distribution drum. This allows the operator to control distribution quantity.



Model	Capacity (Cubic Feet)	Spread Width (Inches)	Drive	Length (Inches)	Width (Inches)	Weight (Pounds)
220	2	20"	Manual	47"	30.5"	85 lbs.
440	4	40"	Electric, Hydraulic	17"	47"	220 lbs.
640	6.5	40"	Hydraulic, PTO	26"	47"	290 lbs.
1140	11	40"	Hydraulic, PTO	33"	47"	355 lbs.
1040SI	10	40"	Electric	57"	47"	300 lbs.
1040B	10	40"	Hydraulic	33"	49"	370 lbs.
1560B	15	60"	Hydraulic	33"	70"	525 lbs.



**BAUMAN**  
MANUFACTURING

3 Industrial Drive, Elmira, ON N3B 2S1 | 519-669-4333 | [baumanmfg.com](http://baumanmfg.com)