

NEW FASTCAT™ PRO

COMMERCIAL ZERO-TURN MOWERS

Rugged DuraDeck™ design, all the way up to a new 61" width, makes the FastCat Pro tough enough to handle everything commercial jobs dish out. Meanwhile, Kawasaki® FX Series engine and a new 2011-compliant fuel system powers this zero-turn mower to higher productivity. Bring it on.

New larger diameter and reshaped motion control levers with new control linkage eliminating lost motion.

Shown with optional folding ROPS.

New custom premium suspension seat with elastameric suspension

Double wave baffles with 22% – 30% larger discharge opening chute

Dual Hydro-Gear ZT-3400 Transaxles are full commercial grade

Large, 23x10:50-12 rear tires for excellent flotation, traction and ride comfort

Front wheels
13x6.50-6 4ply



bobcatturf.com

		FastCat Pro 52	FastCat Pro 61
	Model	942406H	942407H
Engine	Make	Kawasaki FX 691V	Kawasaki FX 730V
	Engine Displacement*	726 cc [44.3cu. in.]	726 cc [44.3cu. in.]
	Lubrication	Full pressure — Spin-on filter	
	Air Filtration System	Dual stage heavy-duty canister air filter	
Deck	Deck Size	52"	61"
	Blade Tip Speed	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
	Deck Design	Fabricated - 2 layers of 10 gauge top deck plus 7-gauge reinforcements – reinforced front lip	
	Deck Skirts	7-gauge skirts	
	Discharge	Double wave baffles with 22% - 30% larger discharge opening and chute	
	Spindle Type	Top mounted 7" diameter — 6 bolt maintenance-free with 1" shaft and split steel pulleys	
	Spindle Bearings	Double-sealed, precision ground ball bearings	
	Cutting Height	1.5" – 4.875"	
	Deck Lift Type	Manual foot lift	
	Deck Drive	175 lb. ft. Warner electric clutch — Single drive belt	
Drive	Transmission	Hydro-Gear ZT-3400	
	Pump Size	12 cc	
	Ground Speed	10 mph	
	Controls	New oversized ProCat control levers	
	Seat	New custom premium suspension seat with elastameric suspension	
Tires	Rear Tires Front Tires	23 x 10.50-12 13 x 6.50-6 4-ply	
	Parking Brake	Internal integrated parking brake	
Fuel	Fuel Capacity	9 Gallons	
	Hour Meter	Digital hour with service reminder	
Size	Height	46" [66" with folding ROPS up]	
	Length	79"	
	Weight/Wet	840 lbs	900 lbs

* Power ratings are provided by the engine manufacturer. Actual power output is dependent upon many factors including engine rpm, air density and engine conditions. For further information, contact Technical Service at Schiller Grounds Care, Inc at 877-596-6337.

Specifications while correct at the time of printing may change without notice.
BOB-CAT® is registered trademark of Schiller Grounds Care, Inc.
© 2011 Schiller Grounds Care, Inc. All Rights Reserved.
One BOB-CAT Lane, Johnson Creek, WI 53038
www.bobcatturf.com • 920-699-2000

SSBCFCPRO5261 1/12

Your Local Dealer is