

FASTCAT™ RZ ZERO-TURN

RESIDENTIAL RELIABILITY

The FastCat RZ is the zero-turn mower that combines traditional BOB-CAT® reliability with the comfort and performance you want for your own property. From Briggs & Stratton® V-Twin Professional Series engines to an all-new optional side back collection system, this is the machine that makes quick work of yard chores. Welcome home.

Adjustable drive levers to fit different family members

.25" increment height of cut lever from 1.5" to 4.875"

Fully adjustable high-back seat with adjustable armrests are spring supported for more comfortable ride



20" drive tire for ground speeds up to 8 mph

The FastCat RZ is covered by a 3-year residential or 90-day commercial warranty.

bobcatturf.com



		FastCat RZ	FastCat RZ	FastCat RZ
	Model	942311G	942313G	942314G
Engine	Make	Briggs & Stratton® V-Twin Professional Series	Briggs & Stratton® V-Twin Professional Series	Briggs & Stratton® V-Twin Professional Series
	Engine HP/ Displacement*	22 HP/721 cc [43.9 cu.in.]	26 HP/721 cc [43.9 cu.in.]	28 HP/821cc [49.4 cu.ft.]
	Lubrication	Full pressure — Spin-on filter		
	Air Filtration System	Standard cartridge type		
Deck	Deck Size	42"	52"	61 "
	Blade Tip Speed	18,809 fpm @ 3550 engine rpm	18,142 fpm @ 3550 engine rpm	18,809 fpm @ 3550 engine rpm
	Deck Design	Fabricated 7-gauge top deck plus 7-gauge reinforcements	Fabricated – 2 layers of 10-gauge top deck plus 7-gauge reinforcements	
	Deck Skirts	7-gauge skirts		
	Spindle Type	Top mounted 7" diameter — 6 bolt maintenance-free with 1" shaft and split steel pulleys		
	Spindle Bearings	Double-sealed, precision ground ball bearings		
	Cutting Height	1.5" - 4.875"		
	Deck Lift Type	Manual with quick-lift-foot assist		
	Deck Drive	125 lb. ft. Warner electric clutch — Singe drive belt		
Drive	Transmission	- Hydro-Gear ZT-2800 hydrostatic drive transaxles - 10 cc variable displacement pump		- Hydro-Gear ZT-3100 commercial-duty hydrostatic drive transaxles - 10 cc variable displacement pumps
	Pump Size	10 cc		
	Ground Speed	8 mph forward/3.5 mph reverse		
Tires	Front Tires	11 x 4.00-5 4-ply		
	Rear Tires	20 x 8-10	20 x 10-10	20 x 10-10
	Parking Brake	Internal integrated parking brake		
Fuel	Fuel Capacity	8.5 Gallons		
	Hour Meter	Digital — Standard		
Size	Height	46" [66" with folding ROPS up]		
	Length	79"	76"	79"
	Weight/Wet	744 lbs	840 lbs	900 lbs

* Power ratings are provided by the engine manufacturer. Actual power output is dependent upon many factors including engine rpm, air density and engine conditions. For further information, contact Technical Service at Schiller Grounds Care, Inc at 877-596-6337.

Specifications while correct at the time of printing may change without notice.
BOB-CAT® is registered trademark of Schiller Grounds Care, Inc.
© 2011 Schiller Grounds Care, Inc. All Rights Reserved.
One BOB-CAT Lane, Johnson Creek, WI 53038
www.bobcatmakeyourmove.com • 920-699-2000

Your Local Dealer is