

PREDATOR-PRO™ ZERO-TURN


NEW FEATURES, MORE PERFORMANCE

The leader of the pack just got more ferocious. We've improved upon the Predator-Pro's ride comfort, discharge design, maintenance access and much more—without disturbing the power and maneuverability that's made this zero-turn mower the popular choice of professionals. And its 2011 EPA-compliant fuel system now holds 14 gallons for fewer stops along the way to increased productivity and industry-leading performance.




Convenient control panel includes new hour meter with maintenance service reminders for engine, hydraulics¹

New ISO-Ride™ Comfort System provides unmatched support plus isolation from shock and vibration¹



16 cc Hydro-Gear Pumps offer speeds up to 13.5 mph and are easily accessible for service



Designed for easy access to maintenance areas like mower deck belt drive, hydraulic oil filter and PTO clutch¹

All-new molded rubber discharge chute with wider deck opening provides improved clipping dispersal¹



PREDATOR-PRO LP

- /// Same comfort and productivity as gasoline-powered Predator-Pro
- /// Work a full day without refueling
- /// Over 50% reduction in ozone-forming exhaust emissions
- /// Standard liquid-feed 35# fork lift tanks, optional with purchase or rotate tanks with liquid propane supplier

No-flat, 13 x 6.50-6 maintenance-free caster tires for better flotation, reduced downtime¹

Up to 7 adjustable anti-scalp front and rear rollers ensure a better cut¹



bobcatturf.com

	Predator-Pro 30 HP LP 61" SD	Predator-Pro 30 HP LP 61" RD	Predator-Pro 30 HP LP 72" SD	Predator-Pro 33 HP 72" SD	Predator-Pro 33 HP 72" SD	Predator-Pro 34 HP 61" SD	Predator-Pro 37 HP DFI 61" SD	Predator-Pro 30 HP 72" SD	Predator-Pro 37 HP DFI 72" SD
	942509G	942510G	942511G	942512G	942513G	942514G	942515G	942516G	942516G
Engine	Generac® Industrial OHVI	Generac® Industrial OHVI	Generac® Industrial OHVI	Generac® Industrial OHVI	Generac® Industrial OHVI	Kawasaki® FX92TV	Kawasaki® FX1000V-DFI	Kohler® Cx750 Command Pro	Kawasaki® FX1000V-DFI
Engine HP/ Displacement*	30 HP/992 cc [60.5 cu. in.]	30 HP/992 cc [60.5 cu. in.]	30 HP/992 cc [60.5 cu. in.]	33 HP/992 cc [60.5 cu. in.]	33 HP/992 cc [60.5 cu. in.]	34 HP/999 cc [61 cu. in.]	37 HP/999 cc [61 cu. in.]	30 HP/747 cc [45 cu. in.]	37 HP/999 cc [61 cu. in.]
Lubrication	Full pressure — Spin-on filter								
Air Filter System	Dual stage heavy-duty canister air filter								
Deck									
Deck Size	61"	61"	72"	61"	72"	61"	61"	72"	72"
Blade Tip Speed	18,854 fpm @ 3800 engine rpm	18,854 fpm @ 3800 engine rpm	18,153 fpm @ 3800 engine rpm	18,854 fpm @ 3800 engine rpm	18,153 fpm @ 3800 engine rpm	18,854 fpm @ 3500 engine rpm	18,854 fpm @ 3500 engine rpm	18,770 fpm @ 3500 engine rpm	18,540 fpm @ 3500 engine rpm
Deck Design	- DuraDeck™ side discharge w/ molded rubber chute - Fabricated dual layer 10-gauge top plus 7- and 3-gauge reinforcements - Reinforced front and side with adjustable front lip	- DuraDeck™ rear discharge molded rubber chute - Fabricated dual layer 10-gauge top plus 7- and 3-gauge reinforcements - Reinforced front and side with adjustable front lip	- DuraDeck™ side discharge tunnel-deck with oversize molded rubber chute - Fabricated, two-layer reinforcements 10-gauge plus 7-gauge - Reinforced front lip and side	- DuraDeck™ side discharge w/ molded rubber chute - Fabricated 7-gauge top plus 7- and 3-gauge reinforcements - Reinforced front and side with adjustable front lip	- DuraDeck™ side discharge tunnel-deck with oversize molded rubber chute - Fabricated, two-layer reinforcements 10-gauge plus 7-gauge - Reinforced front lip and side	- DuraDeck™ side discharge w/ molded rubber chute - Fabricated dual layer 10-gauge top plus 7- and 3-gauge reinforcements - Reinforced front and side with adjustable front lip	- DuraDeck™ side discharge molded rubber chute - Fabricated dual layer 10-gauge top plus 7- and 3-gauge reinforcements - Reinforced front and side with adjustable front lip	- DuraDeck™ side discharge tunnel-deck with oversized molded rubber chute - Fabricated, two-layer reinforcements 10-gauge plus 7-gauge - Reinforced front lip and side	- DuraDeck™ side discharge tunnel-deck with oversize molded rubber chute - Fabricated, two-layer reinforcements 10-gauge plus 7-gauge - Reinforced front lip and side
Deck Skirts & Anti-Scalp Rollers	7-gauge skirts with adjustable anti-scalp rollers front and rear								
Spindle Type	Maintenance-free with 1" shaft								
Bearings	Double-sealed, precision ground ball bearings								
Cutting Height	1.5" - 5.5"								
Deck Lift Type	Manual hand lift with spring assist/RH or LH Quick-Lift foot lift assist								
Deck Drive	Warner Mag Stop 250 ft. lb. electric clutch								
Transmission	Twin Hydro-Gear variable displacement pumps with oil cooler and Parker/Ross wheel motors								
Pump Size	16 cc								
Ground Speed	13.5 mph	13.5 mph	13.5 mph	13.5 mph	13.5 mph	12.5 mph	12.5 mph	12.5 mph	12.5 mph
Tires									
Front Tires	13 x 6.50-6 no-flat caster wheels								
Rear Tires	24 x 12.00-12 4-ply								
Parking Brake	Drum								
Fuel									
Fuel Capacity	14 Gallons								
Hour Meter	Digital hour meter with service minder for engine oil and filter, engine air filter and hydraulic oil and filter								
Machine Length	82"								
Machine Height	49"								
Machine Weight/ Wet	TBD	TBD	TBD	1293 lbs	1404 lbs	1293 lbs	1293 lbs	1404 lbs	1404 lbs
Seat	B-C Lounger high-back with full vibration isolation — Fore and aft adjusters — Quick adjust armrests								

* Power ratings are provided by the engine manufacturer. Actual power output is dependent upon many factors including engine rpm, air density and engine conditions. For further information, contact Technical Service at Schiller Grounds Care, Inc at 877-596-6337.

Your Local Dealer is

Specifications while correct at the time of printing may change without notice.
BOB-CAT® is registered trademark of Schiller Grounds Care, Inc.
© 2011 Schiller Grounds Care, Inc. All Rights Reserved.
One BOB-CAT Lane, Johnson Creek, WI 53038
www.bobcatmakeyourmove.com • 920-699-2000