

HYDROSTATIC WALK-BEHINDS

OUT IN FRONT WITH A GREAT CUT

Take a big step forward in value, control and productivity with a BOB-CAT® hydrostatic walk-behind. Whether you choose the easy-to-use HYDRO WITH Z-CONTROL for zero-turn maneuverability or the rugged BC HYDRO with deck widths up to 54", you'll enjoy all-day comfort and proven performance. They're the walk-behinds that keep you out in front.



New molded rubber chute completes extreme discharge system

7-gauge formed, welded and reinforced construction [36", 48"]. Double 10-gauge steel top on 54" model



Deep-sheave split steel pulleys eliminate belt guides and adjustments



Five-gallon fuel tank means fewer stops and more productivity

Z-CONTROL™ UP-CLOSE

Control your walk-behind just like a zero-turn mower with comfortable, ergonomic levers, easy-to-use speed control bar and reverse assist bar.

Reverse assist bar for smooth operation


Maintenance-free no-flat caster wheels

Dual hydraulic pumps and wheel motor offer ultimate control and productivity



Ergonomic designed levers for zero-turn functionality

Easy-to-use speed control bar



SOFTGRIP™ CONTROLS

SoftGrip™ fingertip controls require minimal pressure to hold. Available in BC HYDRO models.



bobcatturf.com

	Hydro	Hydro	Hydro	Hydro	Hydro	Z-Control Hydro	Z-Control Hydro
	933305G	933307G	934306G	934307G	935308G	935309G	934332G
Engine	Kawasaki® FS481V	Kawasaki® FS541V	Kawasaki® FS541V	Kawasaki® FS541V	Kawasaki® FS600V	Kawasaki® FS600V	Kawasaki® FS541V
Engine HP/ Displacement*	16 HP/603 cc [36.8 cu. in.]	18 HP/603 cc [36.8 cu. in.]	18 HP/603 cc [36.8 cu. in.]	18 HP/603 cc [36.8 cu. in.]	20 HP/603 cc [36.8 cu. in.]	20 HP/603 cc [36.8 cu. in.]	18 HP/603 cc [36.8 cu. in.]
Lubrication	Full pressure — Spin-on filter						
Air Filter System	Dual element air filter						
Deck	Deck Size	36"	48"	48"	54"	36"	48"
	Blade Tip Speed	16,964 fpm @ 3600 engine rpm	15,315 fpm @ 3600 engine rpm	16,964 fpm @ 3600 engine rpm	16,964 fpm @ 3600 engine rpm	15,315 fpm @ 3600 engine rpm	16,964 fpm @ 3600 engine rpm
	Deck Design	- DuraDeck™ side discharge with molded rubber chute - Fabricated 7-gauge top plus 7-gauge reinforcements	- DuraDeck™ side discharge deck with molded rubber chute - Fabricated, two-layer 10-gauge deck top plus 7-gauge reinforcements	- DuraDeck™ side discharge deck with molded rubber chute - Fabricated, two-layer 10-gauge deck top plus 7-gauge reinforcements	- DuraDeck™ side discharge deck with molded rubber chute - Fabricated, two-layer 10-gauge deck top plus 7-gauge reinforcements	- DuraDeck™ side discharge with molded rubber chute - Fabricated 7-gauge top plus 7-gauge reinforcements	- DuraDeck™ side discharge deck with molded rubber chute - Fabricated, two-layer 10-gauge deck top plus 7-gauge reinforcements
	Deck Skirts	7-gauge skirts					
	Spindle Type	Maintenance-free with 1" shaft					
	Spindle Bearings	Double-sealed, precision ground ball bearings					
	Cutting Height	1-3/8" - 4-5/8"					
	Deck Drive	Warner Mag Stop 125 ft. lb. electric clutch					
Drive System	Transmission	Hydro-Gear variable displacement pumps and Parker wheel motors					
	Pump Size	10 cc pumps with separate wheel motors					
	Ground Speed	6 mph					
Tires	Front Tires	9 x 3.50-4 4-No-Flats					
	Rear Tires	16 x 7.50-8 4-ply					
	Brake	Hydrostatic dynamic braking — Dual wheel parking brake					
Fuel	Fuel Capacity	5 Gallons					
Size	Machine Length	78"					
	Machine Height	40.3"					
	Machine Weight/ Wet	528 lbs	528 lbs	582 lbs	593 lbs	524 lbs	596 lbs
							605 lbs

* Power ratings are provided by the engine manufacturer. Actual power output is dependent upon many factors including engine rpm, air density and engine conditions. For further information, contact Technical Service at Schiller Grounds Care, Inc at 877-596-6337.

Your Local Dealer is

Specifications while correct at the time of printing may change without notice.
BOB-CAT® is registered trademark of Schiller Grounds Care, Inc.
© 2011 Schiller Grounds Care, Inc. All Rights Reserved.
One BOB-CAT Lane, Johnson Creek, WI 53038
www.bobcatmakeyourmove.com • 920-699-2000