

## PRESENTING THE CR-10°

From patented technology to built-in versatility, the CR-10 is packed with innovation. Here are a few of the CR-10's unique advantages over other material handlers and topdressers:

- Dual-beam suspension provides lower center of gravity for maximum stability.
- "Fast Attach" system requires no tools when connecting attachments.
- Large, 4-cubic-yard self-cleaning galvanized hopper can be unloaded in less than 30 seconds.
- Unique frame design creates greater clearance for attachments
- ► The rear of the CR-10 raises up to 6 ft for quick loading
- Spinners allow you to set the type of application you want-from very light to medium or heavy-and broadcast width from 20' to 40'





CALL 1-800-679-8201 for a FREE on-site demonstration, or VISIT www.TURFCO.com









## Specifications

Model	CR-10 (#85441 without brakes) (#85440 with surge brakes)
Drive	Tractor's hydraulic system powers belt and attachments
Hopper Capacity	4 yd³ (3.06 m³)
Hopper	Galvanized steel panels
Transport Speed	Up to 8 MPH (12.8 km/h)
Topdressing Speed	Up to 6 MPH (9.6 km/h)
Conveyor Belt	32" (0.81 m) wide, pebble grain surface with heavy-duty polyester cord
Metering Gate	Full manual adjustment with the ability to fully open entire rear hopper panel
Controls	3 position, switch independently operates belt and attachments. Adjustable flow control sets speed of belt and attachments. Adjustable twin spinner sets angle for broadcast topdressing
Wheels & Tires	Four 31" x 15.5"-15" turf tires
Hitch	Heavy-duty pin hitch
Tractor Requirements	Minimum of 35 HP (26 kW) with one bank of hydraulics and 9 GPM flow
Empty Weight	3,600 lb (1,630 kg)
Dimensions	185" (4.7 m) long x 84" (2.1 m) wide x 86" (2.2 m) tall
Options	Surge brakes on two wheels (#85440); Material handler conveyor (#86147); Swivel (#86149); Spinners for topdressing 20' (6.1 m) to 40' (12.2 m) wide (#86174)









