

Redexim



OVERSEEDING



Double Disc Overseeder

The concept of the Double Disc range is to deliver seed into the soil via two rows of discs, in slits 1 inch apart, to ensure maximum germination. They bury the seed up to 3/4-inch deep in the ground, safely away from the weather and the beaks of hungry birds to ensure maximum germination. A massive 6.5 bushel hopper capacity completes the specification. The whole range comes complete with three-point linkage as standard, but a new trailed wheel kit is available as an option.



FEATURE	BENEFIT
Two Rows of Discs	Closer spacing
Massive Hopper	Longer time between refilling
Tight Spacing	Faster recovery and fill in
Wheel Kit	Simple transportation

OVERSEEDING

Double Disc Overseeder



SPECIFICATIONS	DESCRIPTION		
MODEL	1430	1830	2230
Working Width	55" (1.4 m)	72" (1.83 m)	94" (2.4 m)
Weight	2,890 lbs (1,314 kg)	3,506 lbs (1,594 kg)	4,210 lbs (1,870 kg)
Disc Spacing	1.18" (30 mm)	1.18" (30 mm)	1.18" (30 mm)
Cutting Depth	0.25 - 0.8" (5 - 30 mm)	0.25 - 0.8" (5 - 30 mm)	0.25 - 0.8" (5 - 30 mm)
Hopper Capacity	50 gal (230 L)	66 gal (300 L)	79 gal (360 L)
Seed Density	Fully adjustable for any type of seed	Fully adjustable for any type of seed	Fully adjustable for any type of seed
Tractor Required	50 hp, 6,613 lbs (3,000 kg) at ball end lift capacity	60 hp, 7,936 lbs (3,600 kg) at ball end lift capacity	75hp, 9,810 lbs (4,450 kg) at ball end lift capacity
Ground Speed	Up to 7.5 mph (12 kph)	Up to 7.5 mph (12 kph)	Up to 7.5 mph (12 kph)
Capacity	Up to 20,236 sq. yd./h (16,920 sq. m./h)	Up to 26,263 sq. yd./h (21,960 sq. m./h)	Up to 32,291 sq. yd./h (27,000 sq. m./h)
Optional	Trailed wheel kit	Trailed wheel kit	Trailed wheel kit

Accessories

PART #	DESCRIPTION	NOTES	QTY
222.140.002	Bogey Kit 1430	To transfer weight from three point	1
222.180.002	Bogey Kit 1830	To transfer weight from three point	1
222.220.002	Bogey Kit 2230	To transfer weight from three point	1

