

# JACOBSEN<sup>®</sup>

# GK 500<sup>TM</sup>

## Walking Greens Mowers



*The GK 500 series by Jacobsen<sup>®</sup> includes the 518, good for undulating turf, the 522, and the 526 for increased productivity on flat greens and tees. This durable, reliable walking greens mower comes standard with Jacobsen's legendary quality of cut.*

- **InCommand<sup>TM</sup> Control System** - Features user-friendly D-handle with variable speed control and more functional operator presence controls.
- **Precision Balanced** - Precisely balanced for true, straight-line tracking.
- **Optional Turf Groomer<sup>®</sup>** - Improves turf conditions through three-dimensional mowing.
- **Durable Centrifugal Clutch** - Engages easily for smooth operation with no adjustments required.
- **Quiet belt drive system** uses no oils, eliminating leaks on your green.
- **Please Note:** Due to legislation requiring technical manuals to be printed in multiple languages, this product may not currently be available for purchase in all non-English speaking countries. Please contact your nearest distributor or Contact Us for full details.

### QUICK SPECS

**Engine:** Honda<sup>®</sup> GX-120 petrol engine

**Width of Cut:**

**GK 518:** 45.7cm (18") bench setting

**GK 522:** 55.9cm (22") bench setting

**GK 526:** 66.1cm (26") bench setting

**Mow speed:** 5.14km/h (3.2mph)

**Reel blades:** 11 blade (7 blade on GK526)

**Frequency of clip:**

**11 blade:** 4.3mm (.169")

**7 blade:** 6.3mm (.25")

**Check us out!**



[www.ransomesjacobsen.com](http://www.ransomesjacobsen.com)

# GK 500™

## SPECIFICATIONS

Engine	
Type	Honda® GX-120 petrol engine
Horsepower*	2.9 kw (4hp)
Maximum Torque	7.5 Nm (5.4 ft. lbs)
Fuel Capacity	2.5L (.66 gal.)
Traction and Differential	
Reel Drive	Belt Drive
Drive Clutch	Centrifugal
Traction Reduction Ratio	21.8:1
Operator Presence Control	Standard; Controls reels and traction drive
Differential	Full automotive type, housed in traction drum
Reel Drive Drum	Aluminum Alloy
Mowing Speed	5.14km/h (3.2mph)
Traction and Drive	
Traction System	Parallel-series "on demand" 3 WD
Reel Drive	Fixed displacement hydraulic with standard backlap
Hydraulic System	21L (5.5gal.) capacity; 10 micron, full flow filtration; GreensCare™ biodegradable oil
Reels and Blades	
Reel Reduction Ratio	1.67:1
Reel Bearings	Spring-loaded, tapered roller
Reel Diameter	127 mm (5")
Number of Blades	11 (7 on GK526)
Blade Material	Hardened high carbon steel
Cutting Frequency	11 blade: 4.3mm (.169") 7 blade: 6.3mm (.25")
Side Frame Material	Aluminum alloy
Weight and Dimensions	
Weight	GK 518: 95.2kg (210lbs) GK 522: 99.8kg (220lbs) GK 526: 104.3kg (230lbs)
Height-of-cut	GK 518 and 522: 1.6mm – 11.1mm (.062" - .438") GK 522: 1.6mm – 31.8mm (.062" – 1.25")
Width-of-cut	GK 518: 45.7cm (18") GK 522: 55.9cm (22") GK 526: 66.1cm (26")

\*Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

NOTE: Specifications, while correct at time of printing, may change without notice.

## Walking Greens Mowers

## PRODUCT CONFIGURATION

### EQUIPPED STANDARD

- ✓ InCommand control system w/ operator presence control (OPC)
- ✓ Grass catcher
- ✓ Band type brakes
- ✓ Kickstand
- ✓ Honda® gas engine

### ACCESSORIES

- ☐ Front rollers
- ☐ Front roller scrapers
- ☐ Turf Groomer
- ☐ MAGKnife™
- ☐ Fine bristle brush
- ☐ Verticutters
- ☐ LED light kit
- ☐ Transport wheels
- ☐ Mower caddy
- ☐ Mower caddy mounting brackets
- ☐ Push brush