

## PRESENTING THE METERMATIC™ IV.

Turfco's Mete-R-Matic IV topdresser utilize patented ground-drive system. When you speed up, slow down or cross uneven terrain, the conveyor belt and brush automatically adjust at the same rate to provide a consistent and even application every single time. No hydraulics, no pumps and no engines. Just hook up and go.

- ► IDEAL for golf greens, cultured grasses, sports turf and other areas sensitive to weight.
- ► PERFECT for compost or other organic material application.
- ► CONSISTENT. All six wheels drive the machine for consistent application on uneven terrain.
- ► GALVANIZED, wide hopper design is easily loaded with front-end loader or the Turfco\* CR-10.

A simple, versatile, all-around topdresser for all parts of your course...and all types of material? Choose the industry favorite!





CALL 1-800-679-8201 for a FREE on-site demonstration, or VISIT www.TURFCO.com









## **Specifications**

Model	Mete-R-Matic IV (#85424)
Drive	Wheels are driven by the ground; all six tires mechanically drive the conveyor and brush; no engine; no hydraulic system
Hopper Capacity	1 yd³ (.76 m³)
Hopper Size	Top: 73 ½" x 39 ¾" (1.87 m x 1.00 m) Bottom: 60" x 20" (1.5 m x 0.51 m) Depth: 19" (0.48 m)
Spreading Width	60" (1.5 m)
Topdressing Speed	Up to 8 MPH (12.8 km/h)
Transport Speed	Empty: up to 15 MPH (24 km/h) Loaded: up to 8 MPH (12.8 km/h)
Application	From very fine to 1/4" (6.5 mm)
Conveyor Belt	Wide rubber composition with patented Chevron belt 60" (1.5 m)
Metering Gate	Tainter gate design is easily adjusted and provides a uniform opening up to 2 ¼" (57 mm)
Brush	9" (228 mm) diameter, polypropylene bristle
Controls	Electric clutch actuator to engage conveyor and brush. Metering gate control for depth of application.
Clutch	The main clutch is a mechanical ratchet design actuated electrically from the operator's position on the tow vehicle
Wheels & Tires	Six, 16" x 6.50" x 8" rib tread turf tires
Hitch	Heavy-duty pin hitch
Empty Weight	882 lb (400 kg)







