



EASY TO MANUEVER.
REACH MORE **PLACES.**
BE MORE **CONSISTENT.**



PRESENTING THE
METERMATIC™
SELF PROPELLED

#1 in topdressers since 1961: Unparalleled consistency regardless of ground speed combined with a self-propelled design make the Mete-R-Matic® topdresser vital to your business. Easily maneuver across greens and other turf areas to topdress with any material including compost, sand, peat and crumb rubber. Designed with a powered brush and patented Chevron® topdressing belt, it delivers the most precise spread available.

- ▶ **LIGHT FOOTPRINT** - very helpful for new or refurbished greens, reducing the traffic of utility vehicles.
- ▶ **OPERATOR CONTROLS** allow fingertip access to forward, reverse, brakes and throttle.
- ▶ **PLASTIC GUARDS** with insulation for quieter operation.

Easily to maneuver in smaller turf areas and on tighter greens.



CALL 1-800-679-8201 for a FREE on-site demonstration, or **VISIT www.TURFCO.com**





TOPDRESSING:

An important part of turf management.

TURFCO - #1 in topdressing since 1961.

Whether you need to level a lawn, improve drainage or create a seedbed, the Mete-R-Matic Topdresser provides the ultimate in spreading capabilities. From spreading compost to topsoil to sand, the patented Chevron belt and Mete-R-Matic system offers the most precise spread available.

Specifications

Model	Mete-R-Matic (#85417)
Engine	5.5 HP (4.04 kW) Honda® engine with recoil start
Drive	V-belt from engine, roller chain and gear drive to conveyor, traction and brush
Hopper Capacity	11.5 ft³ (0.33 m³), filled level at top of hopper, galvanized panels
Hopper Size	Top: 34 ½" x 39 ½" (0.87 m x 1.00 m) Bottom: 34 ½" x 21 ½" (0.87 m x 0.55 m) Depth: 19 ½" (0.50 m)
Spreading Width	31 ½" (0.8 m)
Topdressing Speed	Up to 2.5 MPH (4 km/h)
Transport Speed	Up to 2.5 MPH (4 km/h)
Conveyor Belt	34"-wide (0.86 m) composition belt with Chevron surface and heavy-duty polyester cord
Metering Gate	Fine adjustment to maximum 3" (76 mm) opening
Brush	9" (228 mm) diameter, polypropylene bristle
Control	Throttle, traction, reverse, brake, engine on/off switch, conveyor drive and metering gate controls; all within easy reach of the operator
Clutch	Dual, V-belt idler clutches for conveyor and traction
Wheels & Tires	Five, 13" x 6.50" x 6" rib thread turf tires
Weight	650 lb (295 kg)

