

95 YEARS OF TRUSTED PERFORMANCE

LITTLE WONDER®

Optimax Blowers

More Air Power. Less Man Power.

Strong, ergonomic adjustable handle with anti-vibration grip for added comfort.



Powerful 7- or 9- blade fan and steel impeller produces high airflow while the scrolled housing allows uninterrupted air intake. Even if a portion of the housing is covered with leaves and debris, airflow can still enter the impeller area and be forced out the discharge chute.

Durable, heavy gauge all-steel housing for strength and durability. Large discharge for optimum air flow.

Curved aerodynamic inlet draws air in smoothly for constant power and helps avoid clogging even if leaves are sucked in.

Convenient lift handle makes lifting the blower on and off the truck easier.



Optional swivel wheel kit for easy maneuverability.

Remote chute deflector control allows you to adjust the split-stream air deflector from the operator's position. (not available on 160 model)



Chain/pulley system controlled from the handle position to adjust the split-stream air deflector.



Optimax™ Self-Propelled Blower

Integrated front/side discharge allows you to expel the air from the front of the unit or out the side without tools.

Split-stream air deflector moves piles of leaves farther and faster without blow-back. You'll only have to go over the area once.

5-YEAR WARRANTY

Engines are warranted separately by manufacturer.



Optimax™ Blower

up to
38% MORE AIR
movement
THAN THE COMPETITION*

**Move leaves, debris, standing water
 and more... Farther and Faster.**

BLOWER SPECIFICATIONS

Push Model Number	9160-02-01	9270-02-01	9270-06-01	9390-02-01	9570-04-01
SP Model Number	N/A	9270-12-01	N/A	9390-12-01	9570-14-01
Engine	Honda® GC160	Honda® GX270	Kohler® Command PRO® CH395	Honda® GX390	Vanguard™
Displacement (cc)	163	270	277	389	570
Fuel Capacity (Gal.)	.83	1.4	1.85	1.6	1.75
Air Cleaner	Foam	Dual Element	Quad-Clean™	Dual Element	
Low Oil Sensor	N/A	Yes			
Impeller Diameter	17" Steel with Integrated Pull Ring	Dual Plane Balanced, 17" Steel with Integrated Pull Ring			
Discharge Chute Area	14.9 sq", 2" Off the Ground	25.8 sq", 2" Off the Ground			
Cfm (Cubic Feet / Min.)	1397	2260		2530	2850
Velocity (Mph)	153	143		160	179
Tires	Pneumatic Tires with Tubes – Sizes may vary by model				
Weight (Lbs.)*	108	142	148	168	188
Travel Speed**	N/A	Variable Speed 0-4.1 mph FWD / 0-2.5 mph REV (self-propelled)			
Warranty***	5-Year				

*Push models only **Self-propelled models only ***Engines warranted separately by engine manufacturer

YOUR LOCAL DEALER IS

***LITTLE
 WONDER®***
Since 1922

Get Proven Results. Get Little Wonder.™

1028 Street Road • Southampton, PA 18966
 1-877-596-6337 • LittleWonder.com