



Zero-Turn Rotary Mower

RZT PRO SERIES™

The MVP of ZT Mowers.

Jacobsen's new **RZT Pro Series** will become a fast favorite of sports turf professionals. It provides the power and performance to handle any turf job with ease.

- **High Horsepower** – Features fuel efficient 25, 27 or 31 horsepower Kawasaki® engine, or 27 or 31 horsepower Kohler® EFI engine to power you up to 6.4 acres per hour.
- **Cutting System** – Offered in three cutting widths (50", 60" and 72"), decks easily tackle large volumes of grass and provide a more attractive after-cut appearance.
- **Superior Mulching** – Add a Twist blade to the existing X-Blade to boost mulching performance.
- **Proven Drivetrain** – Hydro-Gear® pumps and Parker® wheel motors provide smooth and reliable steering.
- **Unique Deck Spindle** – Our standard commercial spindle with an added cooling fan that reduces the operating temperature of the belt and spindle while keeping the top-side of the deck clean.

MODELS:

2550KW: 25hp, 50" Deck

2750 EFI: 27hp, 50" Deck

2760KW: 27hp, 60" Deck


2760 EFI: 27hp, 60" Deck

3172KW: 31hp, 72" Deck


3172 EFI: 31hp, 72" Deck



RZT PRO SERIES
2760KW




50", 60" & 72" Elite X Deck – Cuts all grass types cleanly in any situation.



Open and close the discharge chute on command.



Pumps & Wheel Motors – Stronger transmissions for extended system life.



Heavy-Duty Spindles & Cooling Fans – Keep spindles and belts cool.

*Actual production model may vary.

RZT PRO SERIES™

SPECIFICATIONS

Zero-Turn Rotary Mower

	50" Deck		60" Deck		70" Deck	
Model	2550 KW	2750 EFI	2760 KW	2760 EFI	3172 KW	3172 EFI
Engine						
Manufacturer	Kawasaki® FX	Kohler® EFI	Kawasaki® FX	Kohler® EFI	Kawasaki® FX	Kohler® EFI
Horsepower	25	27	27	27	31	31
Displacement	852cc	824cc	852cc	824cc	852cc	824cc
Air-cleaner	2 stage					
Cooling	Air cooled					
Starter	Electric					
Engine Warranty	3 Year					
Drive System						
Pumps	Hydro-Gear® 12cc					
Wheel motors	Parker® DG240					
Ground speed	11 mph					
Parking brake	Automotive Style					
Towing capacity	500 lbs					
Mower Deck						
Deck size	50"	50"	60"	60"	72"	72"
Acres/hour*	4		5.3		6.4	
Cutting height	1.5" - 4.5"					
OCDC (operator controlled discharge chute)	Standard					
Deck height adjustments	Manual lift, 1/4" increments					
Electric lift	Optional					
Deck engagement	Ogura® 250 ft-lbs					
Construction	10 ga formed & welded				7 ga formed & welded	
Top plate	7 ga bolted (not welded)					
Blades	3 - 17" x 2.5"		3 - 20.5" x 2.5"		3 - 24" x 2.5"	
Spindles	1.25" effective diameter machined shaft					
Spindle housings	Serviceable cast iron					
Spindle cooling fans	1		3			
Anti-scalp rollers			4		5	
Pulleys	Vented split 3/16" steel deep groove					
General						
Battery	12 Volt, 300cca					
Digital display	Tachometer & hour meter					
Fuel capacity	8 gallons					
Rear tires	24 x 12-12 Grass Master					
Front tires	13 x 6.5-6					
Frame	Welded 2" x 2" tube, 7 ga formed					
Fenders	Stainless Steel					
Floor-pan	Flip-up, steel					
Seat	Deluxe (non-suspension) adjustable seat w/ armrest, suspension springs					
Springer forks	Optional		Standard			
Dimensions						
Overall height	50"					
Overall height (rollbar up)	76"					
Overall width	55"		65"		76"	
Overall length			74"		79"	
Overall length (rollbar down)			94"		98"	
Weight	1104 lbs		1215 lbs		1302 lbs	

*Acres/hour at 12mph, 80% efficient

*Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

NOTE: Specifications, while correct at time of printing, may change without notice.

1.888.922.TURF | www.jacobsen.com

