

LAWNNAIRE® IV PLUS AERATOR



The **First Name** in Turf Renovation™

Our Lawnaire® IV Plus aerator is a high-speed, coring, roll-type unit built for the rental industry as well as commercial users with smaller aeration jobs. A fold-down handle and protected lift grabs allow for safer, easier transportation.

New ergonomic features including a more comfortable handle, a handle-mounted throttle and rubber grips make it much easier to operate.

Separate Throttle Control Allows Choice of Speed



COMPACT STORAGE AND TRANSPORT

EASY-TO-USE FEATURES



LAWNNAIRE® IV PLUS AERATOR



The **First Name** in Turf Renovation™



Easy-to-Use Separate Throttle

Handle-mounted design allows you to select any speed you desire



Compact Storage and Transport

Handle quickly folds down for easy transportation or storage



Tough Soil Conditions

Removable weights and fillable water drum add weight for greater tine penetration



HELPFUL HINT: Do not leave drum filled with water for extended periods of time or in cold weather.

HONDA® #744908B	SPECIFICATIONS	BRIGGS & STRATTON® #744909C
GX120 4-cycle	ENGINE	Intek™ 900 4-cycle
0.56 L (0.59 U.S. qt., 0.49 Imp. qt.); 10W-30	ENGINE OIL CAPACITY AND TYPE	0.59 L (0.63 U.S. qt., 0.52 Imp. qt.); 10W-30
Belt tightener	CLUTCH	Belt tightener
Primary – 4L-section V-belt Tine and Drum – Single #40 nickel-plated chain	DRIVE	Primary – 4L-section V-belt Tine and Drum – Single #40 nickel-plated chain
(30) 0.75 in. (19 mm) diameter coring type formed from 0.08 in. (2 mm) hollow, austempered alloy steel	TINES	(30) 0.75 in. (19 mm) diameter coring type formed from 0.08 in. (2 mm) hollow, austempered alloy steel
19 in. (483 mm)	AERATING WIDTH	19 in. (483 mm)
Up to 2.75 in. (70 mm)	CORING DEPTH	Up to 2.75 in. (70 mm)
0.75 in. (19 mm)	CORING DIAMETER	0.75 in. (19 mm)
3.75 in. (95 mm) x 7 in. (178 mm)	AERATION PATTERN	3.75 in. (95 mm) x 7 in. (178 mm)
Up to 9/sq. ft. (0.8 m ² /hr.)	HOLES PER SQ. FOOT (SINGLE PASS)	Up to 9/sq. ft. (0.8 m ² /hr.)
Aerates up to 28,975 sq. ft./hr.	PRODUCTIVITY (EST.)	Aerates up to 28,975 sq. ft./hr.
(2) 8 x 2.5 semipneumatic with ball bearings	TIRES	(2) 8 x 2.5 semi-pneumatic with ball bearings
Dry – 200 lbs. (91.2 kg) Dry with Weights – 254 lbs. (115 kg) Water in Drum with Weights – 280 lbs. (127 kg)	WEIGHT	Dry – 200 lbs. (91.2 kg) Dry with Weights – 254 lbs. (115 kg) Water in Drum with Weights – 280 lbs. (127 kg)
Width – 28 in. (711 mm) Length – 52 in. (1321 mm); 46 in. (1168 mm folded) Height – 48 in. (1219 mm); 30 in. (762 mm folded)	DIMENSIONS	Width – 28 in. (711 mm) Length – 52 in. (1321 mm); 46 in. (1168 mm folded) Height – 48 in. (1219 mm); 30 in. (762 mm folded)
2 year commercial (engines warranted separately from manufacturer)	WARRANTY	2 year commercial (engines warranted separately from manufacturer)



P.O. Box 469, Johnson Creek, WI 53038-0469
©2010 Schiller Grounds Care, Inc. All rights reserved.

Specifications subject to change without notice. See our full line brochure for complete specifications and options.

