

# REN-O-THIN® POWER RAKE



The **First** Name in Turf Renovation™

The Ren-O-Thin® power rake is perfect for dethatching as well as breaking up cores. Its impressive lineup of product features includes a simple-to-operate height adjustment control, heavy tubing on the handle assembly, 4L-section V-belt drive, spring-loaded reel clutch control and interchangeable reels.

A pivoting front axle makes this unit one of the most versatile in its class.

**Pivoting Front  
Axle Design**



**INTERCHANGEABLE  
BLADE REELS**

**PREVENTS SCALPING  
ON UNEVEN TERRAIN**



# REN-O-THIN® POWER RAKE



The First Name in Turf Renovation™

## Simple Height Adjustment

Simple-to-operate adjustment for easy fine-tuning of the cutting depth



## Reversible Handle

Allows you to upmill the turf

## Accessories



1/16" Blades, 1/2" sp. (#547452A)  
1/32" Blades, 3/4" sp. (#547453A)  
1/8" Blades, 2" sp. (#545440A)  
1/8" Flail Blades, 1" sp. (#544440A)

## Maneuverability

Pivoting front axle keeps three wheels on the ground at all times, preventing scalping on uneven terrain



## Easy to Change Reels

Allows you to select blade type and spacing for job



**HELPFUL HINT:** Remember to order your blade set.

HONDA® #744877A	SPECIFICATIONS	BRIGGS & STRATTON® #744865D
GX160 4-cycle	ENGINE	Vanguard™ 4-cycle
0.58 L (0.61 U.S. qt., 0.51 Imp. qt.); 10W-30	OIL CAPACITY	0.59 L (0.63 U.S. qt., 0.52 Imp. qt.); 10W-30
Spring-loaded belt tightener	CLUTCH	Spring-loaded belt tightener
Dual 4L-section V-belt from engine to reel	DRIVE	Dual 4L-section V-belt from engine to reel
Hardened, high-carbon steel	BLADES	Hardened, high-carbon steel
Flail Type 0.125 in. (3 mm) at 1 in. (25 mm) spacing; Fixed Type 0.0625 in. (2 mm) at 1.5 in. (38 mm) spacing; 0.03125 in. (1 mm) at 0.75 in. (19 mm) spacing; and 0.125 in. (3 mm) at 2 in. (51 mm) spacing	REELS	Flail Type 0.125 in. (3 mm) at 1 in. (25 mm) spacing; Fixed Type 0.0625 in. (2 mm) at 1.5 in. (38 mm) spacing; 0.03125 in. (1 mm) at 0.75 in. (19 mm) spacing; and 0.125 in. (3 mm) at 2 in. (51 mm) spacing
Reel adjustable from 1 in. (25 mm) above ground 0.875 in. (22 mm) into ground	CUTTING RANGE	Reel adjustable from 1 in. (25 mm) above ground 0.875 in. (22 mm) into ground
18 in. (457 mm)	OPERATING WIDTH	18 in. (457 mm)
(4) 8 x 1.75 semipneumatic, smooth tread; microscrew adjustment; floating axle to follow contours	TIRES	(4) 8 x 1.75 semipneumatic, smooth tread; microscrew adjustment; floating axle to follow contours
135 lbs. (61 kg)	WEIGHT	135 lbs. (61 kg)
Width – 30 in. (762 mm) Length – 40 in. (1016 mm) Height – 37 in. (940 mm)	DIMENSIONS	Width – 30 in. (762 mm) Length – 40 in. (1016 mm) Height – 37 in. (940 mm)
2 year commercial (engines warranted separately from manufacturer)	WARRANTY	2 year commercial (engines warranted separately from manufacturer)