

## TRACAIRE®

### **SPECIFICATIONS**

#### UNIT

Power	
Lubrication Pressure grease fittings at pivot points	;
HitchStandard 3-point tractor hitch, category "1"	
Aerating Wheel Axle	-
Aerating Wheels	;
pressure lubrication fitting; grooved for mounting aerating	J
tines on both sides; each wheel weighs 75 lb (34 kg)	)
Tines 8 per wheel (96 total); standard one set	į
0.75 in. (19 mm) coring; wheels can be mounted with	1
double set of tines, 16 per wheel (192 total)	)
Coring Depth	)
Aerating Width	)
Aeration Pattern 6 in. x 6 in. (152 mm x 152 mm) with single tines;	;
3 in. x 3 in. (76 mm x 76 mm) with double tines	;
Holes per SqFt	;
up to 18 with double tines	ò
Productivity	)

#### **DIMENSIONS**

Weight
Width
Length
Height

Specifications subject to change without notice.

# The Tracaire 72-inch aerator is the only choice for athletic fields and other large, flat, high-traffic areas with compaction issues.

The austemper-hardened steel tines aerate four inches down into even the most challenging surfaces, allowing deep-rooted grass to prosper in even the harshest conditions. An option of coring, spoon or slicing tines provides versatility, while cast iron tine wheels with sintered bushings add durability and reduce maintenance. Tow the Tracaire aerator with a category "1" 3-point hitch and marvel at its resiliency – not to mention that of the resulting turf's.



TINES

515197\* Tine, Coring 3/4" (19mm), Back

Discharge, Thick Wall

515196 Tine, Coring 1/2" (13mm), Back

Discharge, Thick Wall

520404 Tine, Spoon

**KNIVES** 

521155 Deep Slicing Knife

515193 Shallow Slicing Knife

\*Standard configuration



The cast iron aeration wheels have eight tines per wheel standard. Another eight tines can be installed on the wheel doubling the amount of material removed during coring.



Effortlessly connect the Tracaire to a wide variety of tractors with its durable three-point hitch configuration.

## WWW.RYANTURF.COM