



Zero-Turn Stand-On Mower

# SZT PRO SERIES™

## Stand Up for Speed, Quality, and Reliability.

Jacobsen is proud to introduce the **SZT Pro Series** Stand-on into our commercial line-up. Our newest mower packs power in a small footprint and features:

- **All Muscle** – The new Vanguard® 810cc series provides power and performance in a heavy-duty 26 horsepower engine.
- **Compact Stand-on Design** – The SZT's small footprint allows it to maneuver in tight areas and take up less trailer space.
- **Industrial Strength** – Forged from 7-gauge steel, the SZT is built for the rigors of commercial mowing.
- **Versatile Design** – Flip up the operator platform to use the SZT as a conventional walk-behind, giving you more mowing options.
- **Deeper Deck** – The deep deck features a 7-gauge steel shell and can easily handle large volumes of grass without slowing you down.
- **Built-In Footsteps** – Allows you to shift weight balance for better traction along hillsides.

### MODELS:

**SZT 2648: 26hp, 48" Deck**

**SZT 2654: 26hp, 54" Deck**

\*Actual production model may vary.




**SZT PRO SERIES 2654**



**Vanguard® Engine** – 26 HP commercial engine.




**OCDC** – Open and close the discharge chute on command.



**Hydro-Gear® ZT-3400** – Commercial-grade transmission with serviceable filter.



**Hillside Footsteps** – Keep your balance while accessing hillsides.



**48" and 54" V6 Cutting System** – Deeper deck for cutting thick grass.

# SZT PRO SERIES™

## Zero-Turn Stand-On Mower

### SPECIFICATIONS

Model	2648	2654
Engine		
Manufacturer	Vanguard®	
Horsepower	26	
Displacement	810cc	
Air-cleaner	2 stage	
Cooling	Air cooled	
Starter	Electric	
Engine warranty	3 Year	
Drive System		
Dual Hydrostatic	Hydro-Gear® ZT-3400	
Ground speed	8 mph	
Parking brake	Integrated in transmission	
Mower Deck		
Deck size	48"	54"
Acres/hour	3.1	3.7
Cutting height	1.5" - 5"	
OCDC (operator controlled discharge chute)	Standard	
Deck height adjustments	Manual lift, 1/4" increments	
Electric lift	Optional	
Deck engagement	Ogura® 150 ft-lbs	
Construction	7 ga formed & welded	
Top plate	7 ga bolted (not welded)	
Blades	3 - 17.875" x 2.5"	3 - 21.375" x 2.5"
Blade tip speed (approximate)	17,875 fpm	17,399 fpm
Spindle housings	1pc keyless sealed cast iron	
Spindles	1.25" Effective diameter machined shaft	
Anti-scalp rollers	4	
Pulleys	Vented split 3/16" steel deep groove	
General		
Battery	12 Volt, 300cca	
Digital display	Tachometer, voltmeter, service alerts	
Fuel capacity	6 gallons	
Rear tires	23 x 9.5-12 Grass Master	23 x 10.5-12 Grass Master
Front tires	15 x 6-8 Semi-Pneumatic / Flat Proof	
Frame	Welded 2" x 2" tube, 7 ga formed	
Operator Platform	Flip-up, steel	
Springer Forks	Optional	
Dimensions		
Overall height	48"	
Overall width (with chute up)	49"	55"
Overall width (with chute)	64"	70"
Overall length	67.5"	
Overall length (platform down)	79"	
Weight	824 lbs	844 lbs

\*Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

NOTE: Specifications, while correct at time of printing, may change without notice.

1.888.922.TURF | [www.jacobsen.com](http://www.jacobsen.com)

