



SAND STAR "ZEE" Golf Bunker Rake

MODEL	45-501 Sand Star ZEE
POWER	22hp (16.4 kW) Briggs & Stratton Commercial Turf V twin cylinder , air cooled, gasoline (724 cc) displacement, electronic ignition Full pressure lubrication with oil filter Engine mounted cyclonic two-stage air cleaner with replaceable element.
DRIVE	Belt drive with independent infinitely variable unitized transmission.
SPEED	Infinitely variable from 0 – 10 mph (16 kph) forward; 0-4 mph (6 kph) reverse
BRAKING	Dynamic braking through the hydrostatic transmission Hand operated park brake. Drum brakes on rear wheel
CONSTRUCTION	Heavy gauge steel tubing, hydraulically formed, electrically welded.
TIRES/WHEELS	(2)25 x 10 x 12 knobbed tires on rear (1) 16 x 7.50 - 8 Front castor wheel
STEERING	Power steering, controlled through two independent control sticks with integrated dampeners. Zero turning radius.
CONTROLS	Throttle, choke, hour meter and safety interlock switch for startup.
SEAT	High back cushioned adjustable deluxe seat with integrated arm rests and retractable seat belts.
ELECTRICAL	12 volt battery operator presence switch in seat.
SOUND LEVEL	88dBA
DIMENSIONS (Inches/cm) (Length-Width-Height)	75 in (191 cm)-59 in (150 cm)-70 in (178 cm);
WEIGHT	880 lbs (399 kg)
LIQUID CAPACITIES	Gasoline (unleaded): 5 gallons (19 liter) in high density, nylon, low-perm tank Hydraulic system oil: 1.75 gallons (6,6 liter) required in high density polyethylene tank
SAFETY & CONFORMANCE	Complies with all applicable ANSI and OSHA Smithco Engineered Operator Protective Structure
IMPLEMENTS	Many efficient and effective implements for constructing and maintaining bunkers and surrounding areas Rear Attachment Lift - Electric-Hydraulic thumb switch operated Center Lift - Manual lift with automatic Lock. Foot operated. Adjustable depth control.