

Tournament Ultra Greens Roller 7580 Tournament Ultra Plus Greens Roller 7590

POWER 16hp (12 kW) Vanguard V twin cylinder, air cooled, gasoline, cast iron sleeves, 29.3 cu.

In. displacement, electronic ignition, full pressure lubrication with oil filter, engine

mounted air cleaner

CONFIGURATION A golf course greens roller using (2) 8.75" (22.225 cm) roller cylinders

Operated from side-to-side by seated operator

DRIVE Hydrostatic power using 12 cc displacement hydraulic pump driving (1) hydraulic

drive motor on each roller.

SPEED Infinitely variable, 0-12 mph (0-16 kph) in each direction

BRAKING Dynamic braking through the hydrostatic drive system

BATTERY Automotive type 24F, 12 volt,

CONSTRUCTION Heavy gauge square steel tubing, hydraulically formed, electrically welded.

ROLLERS All steel, seamless, drawn over mandrill tube

(2) 8 in (20 cm) steel powder coated rollers 36 in (91 cm) long Bolt on hubs with bearings on each end of each cylinder

STEERING Tournament Ultra - 10.2 x 1 reduction, 16 in (40 cm) automotive type steering wheel

10' (3m) diameter turning radius

Tournament Ultra Plus – power steering with orbitrol motor.

GROUND PRESSURE Variable with ground conditions, typical is 4.5 PSI

HILL CLIMBING ABILITY Up to 40%

CONTROLS Foot controlled, variable speed in both directions (Operator's left; Operator's right)

Dual pedal for left / right travel

SEAT High-back, one piece for operator comfort

ELECTRICAL 12 volt electric start

SOUND LEVEL At Ear level - 72 dBA

DIMENSIONS (Inches/cm)

(Length-Width-Height)

Length – 52 in (132 cm), Width – 49 in (125 cm), Height – 47 in (119 cm)

WEIGHT 900 lbs (408 kg)

LIQUID CAPACITIES Hydraulic Fluid: 5 gallon (19 l) in high density polyethylene tank

Fuel Capacity: 5 Gallon (19 I.) in high density polyethylene tank

SAFETY & CONFORMANCE

CONFORMANCE

Complies with all applicable ANSI and OSHA specifications

Operator presence switch in seat for engine start

Complies with applicable requirements of European Machinery Directive (#7540 only)

TRANSPORT Dedicated trailer 7505

Width - 56 in (142 cm); Length - 48 in (121 cm); with tailgate up not including tongue-

Height – 9 in (22 cm) Side rails Hitch Height – 16 in (40 cm) Weight – 240 lbs. (528 kg) Tires – (2) 18- 9.50 x 8 Axle – Spindles with hubs

Drawbar Length – 44 in (111 cm) – 47 in (119 cm)