

# Redexim



## OVERSEEDING



Speedseed

# 2100

The new Speedseed models 2100 and 2400 are ideal to over-seed large areas quickly. The front spiked roller made of individual cast rings creates thousands of holes and can easily turn along any obstacles in its path. This seeder is designed for the professional turf manager that prefers not to see the traditional rows created by other machines on the market.

FEATURE	BENEFIT
Spike Roller	Thousands of holes
Individual cast rings	Easy replacement
Wider working width	More productive
Accurate seeding system	Less waste and better germination






## OVERSEEDING

# Speedseed 2100



SPECIFICATIONS	DESCRIPTION
Working Width	83" (2.1 m)
Weight	1,375 lbs (625 kg)
Number of holes with one spiked roller	1,124/sq. yd. (940/m²)
Number of holes with two spiked rollers	2,201/sq. yd. (1840/m²)
Hopper capacity	10.66 cu. ft. (300 L)
Seed density	fully adjustable
Tractor required	35 hp 1,760 lbs (800 kg) Lift Cap
Ground speed capacity	up to 6 mph (10 km/h)
Optional	- 2nd Spiked Roller weighing 282 lbs (138 kg) - tines for rear roller (more holes per sq. ft.)

### Delivering the most seed



The spikes



Holes

The spikes are conical shaped, so that more seed actually drops into the holes. The seed drops when the side wheel turns, so no spillage of seed when the machine is not in operation. Optional, a 2nd roller with spikes can be added for doubling the amount of holes per pass.





# Redexim



## OVERSEEDING



Speedseed

# 2400

The new Speedseed models 2100 and 2400 are ideal to over-seed large areas quickly. The front spiked roller made of individual cast rings creates thousands of holes and can easily turn along any obstacles in its path. This seeder is designed for the professional turf manager that prefers not to see the traditional rows created by other machines on the market.



FEATURE	BENEFIT
Spike Roller	Thousands of holes
Individual cast rings	Easy replacement
Wider working width	More productive
Accurate seeding system	Less waste and better germination




## OVERSEEDING

# Speedseed 2400



SPECIFICATIONS	DESCRIPTION
Working Width	94" (2.4 m)
Weight	1,654 lbs (750 kg)
Number of holes with one spiked roller	1,124/sq. yd. (940/m²)
Number of holes with two spiked rollers	2,201/sq. yd. (1840/m²)
Hopper capacity	12 cu. ft. (336 L)
Seed density	fully adjustable
Tractor required	40 hp 2,090 lbs (850 kg) Lift Cap
Ground speed capacity	up to 6 mph (10 km/h)
Optional	- 2nd Spiked Roller weighing 348 lbs (158 kg) - tines for rear roller (more holes per sq. ft.)

### Delivering the most seed



The spikes



Holes

The spikes are conical shaped, so that more seed actually drops into the holes. The seed drops when the side wheel turns, so no spillage of seed when the machine is not in operation. Optional, a 2nd roller with spikes can be added for doubling the amount of holes per pass.

