

JACOBSEN[®]

TR-3[™]

Trim Mowers

The TR-3[™] is a world class cutting and climbing reel trim mower. It hugs contours with ease and provides Jacobsen's legendary quality-of-cut on even the steepest of hills. The full-time all wheel drive traction, weight transfer control and reliable braking allow operators to mow with confidence and tackle tough terrain. Designed for tee boxes, approaches and surrounds where high level power and quality is needed.



TR-3 with 7 blade reel and grooved front rollers



Factory-filled with GreensCare[™] Biodegradable Hydraulic Fluid

- **Parallel-Series 3WD traction system** provides grip on hilly terrain and damp working conditions ensuring a wheel will keep footing and maintain productivity.
- **On-demand weight transfer control** allows operator to shift additional flow to wheels for maximum hill climbing power.
- **The all-out-front design with forward seating position** supplies operator with unobstructed sight lines of the cutting path.
- **Heavy-duty and proven Jacobsen Classic XP[™] reels** produce exceptional cut quality.
- **Operator ergonomics and safety** come standard with the smooth foot-pedal transmission, power steering, adjustable steering wheel, high-back suspension seat and operator protection structure with seat belt.
- **Oil-immersed maintenance free parking brakes** deliver safe braking on even the steepest of slopes and reduce total cost of ownership with no linkage or pads to service or adjust.

QUICK SPECS

Engine: Kubota[®] diesel

Cutting Units: Three 17.8 cm (7") x 66cm (26")

Height of Cut: 9.5 - 69.8mm (0.37" - 2.75")

Width of Cut: 1.83m (72")

Dimensions:

Weight: 930kg (2050lbs.)

Length: 2.65m (104.3")

Height: 1.82m with OPS (71.7")

Width: 2.02m (79.5")

Check us out!



www.ransomesjacobsen.com

TR-3™

SPECIFICATIONS

Engine	
Type	Kubota® D1105-E 3-cylinder diesel
Rated Horsepower*	18.6kW (24.8hp) @ 3000 rpm
Displacement	1,123cc (68.55 cu. in.)
Air Cleaner	Dry Cartridge type
Cooling System	Pressurized, sealed cooling system; coolant capacity: 5.3L (1.4gal.)
Lubrication	Pressurized system with replaceable full flow filter
Fuel Capacity	45.4L (12gal.)
Oil Filter Type	Replaceable spin on type
Electrical System	0.8kW (12V) starter; 40 amp alternator/regulator
Speed (Maximum)	
Mowing	9.7km/h (6mph)
Transport	14km/h (8.7mph)
Reverse	6km/h (3.7mph)
Traction and Drive	
Traction System	Parallel-series, Full-time 3WD
Reel Drive	Fixed displacement hydraulic with optional backlap
Hydraulic System	6.6 gal. (25 L) capacity; hydraulic oil monitor and horn alarm; GreensCare™ 68 biodegradable oil
Tyres, Brakes and Steering	
Front Tyres	Two 20 x 12-10, Turf Trac 4-ply
Rear Tyres	One 20 x 10-8, 4-ply
Service Brakes	Dynamic braking through hydrostatic drive
Parking Brake	Hydraulic wet park brake integrated in the front wheel motor
Steering	Hydraulic power steering with tilt wheel
Reels and Blades	
Number and Size	Three 17.8cm (7") diameter, 66cm (26") 7-blade reels
Blade Material	Hardened, high manganese carbon steel
Overall Cutting Width	1.83m (72")
Cutting Unit Lift	Joystick actuated with cross-cut lift position
Weight Transfer	Adjustable hydraulic weight transfer - electronically activated at operator controls
Height-of-Cut	9.5 - 69.8mm (0.37-2.75")
Cutting Capacity	1.8ha/hr (4.4 acres/hr) at 9.7km/h (6mph)
Weight and Dimensions	
Weight	930kg (2050lbs.)
Length	2.65m (104.3")
Height	1.82m (71.7") with OPS
Wheelbase	1.51m (59.75")
Width	2.02m (79.5")

*Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

NOTE: Specifications, while correct at time of printing, may change without notice.

Trim Mowers

PRODUCT CONFIGURATION

EQUIPPED STANDARD

- ✓ Operator Protection Structure (OPS) with seat belt
- ✓ GreensCare biodegradable hydraulic fluid

CUTTING UNITS

- ☐ 7 blade reel, 17.8cm (7") diameter x 66cm (26"), including solid tube steel rear roller (LH, RH, Centre)

ACCESSORIES

- ☐ 66cm (26") Grooved steel front rollers (set of 3)
- ☐ Grooved front roller scraper bars (set of 3)
- ☐ Rear roller scraper bar
- ☐ Grass catchers, gray with hardware (set of 3)
- ☐ Backlap valve kit
- ☐ Work lights / Headlights
- ☐ Canopy / Sunshade

GENUINE SERVICE PARTS

- ☐ Classic XP reels: 7 & 10 blade
- ☐ Heavy section Legendary™ Bedknives
- ☐ Heavy section MAGKnife™
- ☐ GreensCare 46 and GreensCare Plus 46 biodegradable fluid



+44 (0) 1473 270 000 | www.ransomesjacobsen.com

© 2016 Jacobsen - A Textron Company/Textron Innovations Inc. All rights reserved.