



COVER MORE GROUND
AND GET **BETTER**
GERMINATION RATES.

TURFCO®

PRESENTING THE
TRIWAVE™ 60.

Golf course superintendents told us they wanted a seeder with better germination rates, but minimal turf disruption. Four patents later, the TriWave™ 60 delivered on that promise. Three floating heads follow the contour of the ground while the unique seed delivery system works with the WaveBlade technology to optimize seed-to-soil contact for maximum germination rates—all while minimizing turf disruption.

- ▶ **60-INCH APPLICATION WIDTH** combines with close, 1½-inch spacing to give you the most productive, high-germination rate seeder available.
- ▶ **DEPTH ADJUSTER** allows you to adjust to varying conditions or seed types in the field without tools.
- ▶ **PATENTED FLOATING HEADS** and WaveBlade technology combine to ensure you won't damage sprinkler heads or other unmarked items.

Created with the help of superintendents, it delivers the results they – and you are looking for.



CALL 1-800-679-8201 for a FREE on-site demonstration, or **VISIT www.TURFCO.com**

TURFCO



Specifications

Model	TriWave 60 Overseeder (#85851)
Width	74" (1.88 m)
Height	51" (1.3 m)
Length	40" (1.02 m) <i>without PTO shaft</i>
Capacity	4.77 ft ³ (8,251 in ³)
Application Pattern	Seed spacing 1 1/2" (38.1 mm) apart
Application Width	60" (1.52 m)
Seed Gate	Manually operated, variable opening
Ground Speed	Up to 5.5 MPH (8.85 km/h)
Productivity	Up to 3 acres per hour
Cutting Heads	3 heads, independently floating
Blade Assembly	3 WaveBlade sets, total 30 blades
Blade Assembly Operating Depth Range	0 to 1 3/8" (0 to 34.9 mm)
Tractor/Horsepower Requirements	35 HP minimum to 60 HP maximum (26.1 kW to 44.7 kW)
Drive	540 PTO (tractor)
Hitch Type	Category 1 or Category 2, 3-pt. hitch
Weight	1,150 lb (521.6 kg) <i>hopper empty</i>
Maximum Weight with Seed Hopper Full	Approximately 1,250 lb (567 kg)

