


Redexim



A E R A T I O N



Verti-Drain


7215

Building on the tradition of innovative excellence, the Verti-Drain 7215 incorporates the technology of the second-generation line with new and improved features. The 7215 boasts a working width of 61" (1.56m) and can aerate up to 10" (250mm) maximum, making for greater productivity when fit to a 25 hp tractor.

| FEATURE | BENEFIT |
|--|--|
| Unique adjustable parallelogram forced heave | Shatters compaction in any ground conditions. Versatile with single-point adjustment for optimum results and hollow coring |
| 3-speed gearbox | Matches your tractor's ground speed exactly to achieve desired hole spacing. Creep speed tractor gear not essential |
| Sealed bearings not bushings | Long maintenance free life |
| Higher working speed | Greater working capacity |
| Useable playing surface | Aerate at any time without interruption of play |

AERATION

Verti-Drain 7215



| SPECIFICATIONS | DESCRIPTION |
|---|--|
| Working width | 61" (1.56 m) |
| Working depth | Up to 10" (250 mm) |
| Tractor speed@500 rev's at PTO Spacing 2 1/2" (65 mm) Spacing 4" (100 mm) Spacing 6 1/2" (165mm) | - Up to 0.60 mph (1.00 km/h) Up to 1.00 mph (1.50 km/h) Up to 1.60 mph (2.50 km/h) |
| PTO speed: (max) | Up to 500 rpm |
| Weight | 1,210 lbs (550 Kg) |
| Hole spacing side-to-side | 4" (100 mm) @ 3/4" (18 mm) holes 2.5" (65 mm) @ 1/2" (12 mm) holes |
| Hole spacing in driving direction | 1" - 6 1/2" (25 - 165 mm) |
| Recommended tractor size | 25 HP with lift capacity of minimum 1,540 lbs (700 Kg) |
| Capacity (maximum) Spacing 2 1/2" (65 mm) Spacing 4" (100mm) Spacing 6 1/2" (165mm) | - Up to 16,813 sq ft (1,563 sq m)/ hour Up to 25,866 sq ft (2,404 sq m)/ hour Up to 42,678 sq ft (3,966 sq m)/ hour |
| Shipping dimensions | 69" x 32" x 44" (1.7m x 0.8m x 1.1m) |
| Maximum tine size | Solid 3/4" x 10" (18 x 250 mm) Hollow 1" x 10" (25 x 250 mm) |
| Three point linkage | 3- point CAT 1 |
| Standard items | Set solid tines to 1/2" x 10" (12mm x 250mm) Front and rear roller 3- shuttle gearbox |

Accessories

| PART | DESCRIPTION | NOTES | QTY |
|-------------|--------------------|---|-----|
| 211.721.002 | Turf Hold Down Kit | Aligns with 12mm tineholder holes | 1 |
| 211.721.004 | Turf Hold Down Kit | Aligns with 18mm tineholder holes | 1 |
| 211.721.006 | Core Collector | Pulls cores to end of pass | 1 |
| 211.721.016 | Windrow Kit | Funnels cores into a straight line behind machine | 1 |
| 314.425.170 | Needle Tine Block | Holds twenty-one 3/16" tines | 8 |
| 9990206 | Pencil Tine Block | Holds six 8mm shank tines | 8 |

Tine Selections

The 7215 offers reinforced front and rear rollers, as well as a lighter frame than the 73 series, thus having lower horsepower requirements.

| PART # | DESCRIPTION | DEPTH | TOTAL | ID | OD | WALL | CORE | MOUNT | QTY. |
|---------------------|---------------------|-------|--------|------|-------|------|------|-------|----------|
| SOLID TINES | | | | | | | | | |
| 311.112.200 | 1/2 x 8 # | 8 | 10 | na | 12mm | na | na | 12mm | 24 |
| 311.118.200 | 3/4 8 | 8 | 10 | na | 18mm | na | na | 18mm | 16 |
| 2381837 | 1/2 x 10 # | 10 | 12-1/2 | na | 12mm | na | na | 12mm | 24 |
| 2381841 | 3/4 x 10 | 10 | 12-3/4 | na | 18mm | na | na | 18mm | 16 |
| 311.112.150 | 1/2 x 6 | 6 | 8 | na | 12mm | na | na | 12mm | 24 |
| 311.108.150 | 5/16 x 6 | 6 | 8 | na | 8mm | na | na | 8mm | 24M/48* |
| 311.105.125 | 3/16 x 5 | 5 | 5-3/4 | na | 5mm | na | na | 5mm | 24N/168* |
| 9990056 | 5/16 x 7 | 7 | 9 | na | 8mm | na | na | 8mm | 24M/48* |
| 9990059 | 5/16 x 10 | 10 | 11-1/2 | na | 8mm | na | na | 8mm | 24M/48* |
| CORING TINES | | | | | | | | | |
| 311.210.080 | 3/8 x 3-1/4 | 3-1/4 | 4-1/4 | 5/1 | 3/8 | .045 | 1/4 | 8mm | 24M/48* |
| 311.210.127 | 3/8 x 5 | 5 | 6 | 5/16 | 3/8 | .047 | 1/4 | 8mm | 24M/48* |
| 9990022 | 5/8 x 7 | 7 | 8 | 1/2 | 5/8 | .062 | 3/8 | 12mm | 24 |
| 9990023 | 3/4 x 10 | 10 | 11-3/4 | 9/16 | 3/4 | .094 | 7/16 | 18mm | 16 |
| 9990024 | 1 x 10 | 10 | 11-3/4 | 9/16 | 3/4 | .094 | 7/16 | 18mm | 16 |
| 9990040 | 3/4 x 10 | 10 | 11-1/2 | 9/16 | 3/4 | .094 | 7/16 | 12mm | 24 |
| 9990076 | 1 x 6 | 6 | 7 | 3/4 | 1 | .125 | 5/8 | 12mm | 24 |
| 999F003 | 13/16 x 6 | 6 | 7-3/8 | 9/16 | 13/16 | .105 | 1/2 | 12mm | 24 |
| 999F005 | 5/8 x 6 | 6 | 7 | 1/2 | 5/8 | .062 | 3/8 | 12mm | 24 |
| 999F007 | 5/8 x 6 fixed shank | 6 | 7 | 1/2 | 5/8 | .062 | 3/8 | 12mm | 24 |
| ADAPTORS | | | | | | | | | |
| 314.208.043 | M-8mm to 12mm | na | na | 8mm | 12mm | na | na | na | 24 |
| 314.205.043 | N-5mm to 12mm | na | na | 5mm | 12mm | na | na | na | 24 |
| 311.812.120 | X-1/2 Verti-Drill | na | na | 1/2 | na | na | na | 12mm | 24 |
| VERTI-DRILLS | | | | | | | | | |
| 311.812.230 | 1/2 x 10 Drill | 10 | 10.5 | na | 1/2 | na | na | 12mm | 24x |

