

Redexim



SYNTHETIC TURF



Verti-Top 1800

Regular maintenance of synthetic turf is necessary to keep playing surfaces clean, bacteria-free and allow water infiltration. The Verti-Top 1800 employs a highly effective synthetic rotary brush to remove debris and top layer infill from the turf, then sifts the debris out in a unique vibratory shaker which redistributes the clean infill back on the field. Finishing the work is a rear lag brush, leaving a clean and smooth playing surface. Now with Vacuum Attachment.

FEATURE	BENEFIT
Wider working width	More productive
Softer long lasting brush	No damage to field
Front Casters	Does not roll or skip lighter turf
Vacuum Attachment	Collects finer material such as dust, hair and pollutants



SYNTHETIC TURF

Verti-Top 1800



SPECIFICATIONS	DESCRIPTION
Working width	70.9" (1.8m)
Working depth	Up to 1.02" (26mm)
Speed	Maximum 7.5 mph (12 km/h)
Weight	970lbs (440 Kg)
Tractor recommended	25 HP with minimum lifting capacity of 480 kg
Collection Hopper Capacity	0.95 cu.ft. (3x 27 litres)
Maximum capacity	96875ft² (9000m²)
Mesh of sifting screens (Standard supplied)	0.2" x 0.2" (5 mm x 5 mm)
Three-point connection	Cat. 1, Cat. 2
Standard items	<ul style="list-style-type: none"> - Easy to change and adjust the shaking sieve 0.2" x 0.2" (5 mm x 5 mm) - Sliding brush - Integrated adjustable rake - 3 waste receptacles - PTO axle
Optional	Shaking sieves: <ul style="list-style-type: none"> - 0.13" x 0.13" (3.2mm x 3.2mm) - 0.16" x 0.16" (4mm x 4mm) - 0.2" x 0.2" (5 mm x 5 mm) - 0.22" x 0.22" (5.5mm x 5.5mm) - 0.24" x 0.24" (6mm x 6mm)

