



## **ZT400**<sup>TM</sup>

### Dependable Performance. Professional Results.

The new Jacobsen ZT400 Series delivers the productivity, quality, and reliability expected with over 95 years of industry leading turf innovation.

- High Horsepower Features fuel efficient engines from Briggs & Stratton® and Kawasaki® to power you through up to 4.3 acres per hour.
- Cutting System Offered in three cutting widths (48-, 54- and 60-inch), decks easily tackle large volumes of grass and provide a more attractive after-cut appearance.
- Proven Drivetrain Parker® HTE transmissions provide smooth, reliable steering and are up to 15% more fuel efficient than the competition.
- Robust Deck Spindle The Turf Xtreme™ spindles are maintenance free and provide longer bearing life with Contamination Exclusion Technology. The high-strength ductile iron is 60% stronger than aluminum housings.
- Optional Accessories Add an electric deck lift for easy deck height adjustments, or a foot-operated Operator Controlled Discharge Chute for opening and closing the discharge chute on the fly.

#### ZT400 MODELS:

2248KW: 22 hp, 48-inch Deck 2454KW: 24 hp, 54-inch Deck **2554BR:** 25 hp, 54-inch Deck **2460KW:** 24 hp, 60-inch Deck **2560BR:** 25 hp, 60-inch Deck

\*Actual production model may vary.



**ZT400** 2460KW




InCommand Console - Keyless ignition. "SoftStart"clutch engagement, and more



Parker® HTE - Quiet, and efficient transmissions provide an extended life and smoother drive



PEER® Spindles - Sealed with Contamination Exclusion



Perfect Tension™ – Constant belt tension to increase belt life Technology for reliable performance expectancy up to three times

# **ZT400**<sup>TM</sup>

#### **PRELIMINARY SPECIFICATIONS**

### **Product Preview**

	48-inch Deck	54-inch Deck		60-inch Deck	
Model	2248KW	2454KW	2554BR	2460KW	2560BR
Engine	-				
Manufacturer	Kawasaki <sup>®</sup> FS		Briggs & Stratton® Cyclonic®	Kawasaki® FS	Briggs & Stratton® Cyclonic®
Horsepower	22 hp	24 hp	25 hp	24 hp	25 hp
Displacement	726cc	·	724cc	726cc	724cc
Air-cleaner	2 stage		5 stage	2 stage	5 stage
Cooling	Air cooled				
Starter	Electric				
Engine warranty	3 Year				
Drive System					
Dual hydrostatic	Parker® HTE				
Ground speed	9 mph				
Parking brake	Integrated in transaxle				
Towing capacity	200 lbs				
Mower Deck					
Deck size	48 in	54 in		60 in	
Acres/hour	3.4	3.9		4.3	
Cutting height	1 in - 5 in				
OCDC (operator controlled			Fact approted (antique)		
discharge chute)	Foot-operated (optional)				
Deck height adjustments	Manual lift, 1/4 in increments				
Electric lift	Optional				
Deck engagement	Ogura® 150 ft-lbs				
Construction	7 ga formed & welded				
Blades	(3) -2.5 in x 17.25 in	(3) - 2.5 in x 19 in		(3) - 2.5 in x 20.5 in	
Blade tip speed (approximate)	18,398 fpm	18,257 fpm 18,541 fpm			
Spindles	1 in effective diameter machined shaft				
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)				
Anti-scalp rollers	4				
Pulleys	7 ga steel deep groove				
General					
Battery	12 Volt, 300cca				
Digital display	InCommand™ Console - Tachometer, hour meter, fuel gauge, engine warnings, ignition				
Fuel capacity	6.8				
Rear tires	23 x 9.5-12 GrassMaster 23 x 10.5-12 GrassMaster				
Front tires	13 x 6.5-6				
Frame	Welded C-channel, 7 ga formed				
Floor-pan	Removable, steel				
Seat	Deluxe (non-suspension) adjustable seat w/ armrest, suspension springs				
Springer Forks	Optional accessory				
Dimensions					
Overall height (rollbar down)			50 in		
Overall height (rollbar up)	71 in				
Overall width (chute down)	63.6 in	69.6 in 76 in			'6 in
Overall width (chute up)	49.2 in	55.4 in		61.9 in	
Overall length (rollbar down)	85.8 in				
Overall length (rollbar up)		81.3 in			
Overall leftgut (rollbat up)					

Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

NOTE: Specifications, while correct at time of printing, may change without notice.



JACOBSEN'

<sup>\*</sup>Acres/hour at top speed and 80% efficient