

# **GREENS OVERSEEDER**

**SPECIALLY DESIGNED FOR BENTGRASS SEED**



**PROFESSIONAL TURF CARE EQUIPMENT**

**AgriMetal**



# Greens over seeder Model W-24

Agrimetal has found solutions to deal with persistent problems to greens over seeding. The problems consist of wide spacing between rows which take forever to fill in. Low germination caused by ineffective placement of the seed in the trench. Excessive damage caused by the blades during single and diamond pattern seeding.

Agrimetal has designed an over seeder that eliminates the problems that superintendents have been battling with for over 25 years

A regular seeding pattern at  $\frac{3}{4}$  inch from center to center. Notice the clean slitting without any thatch or debris allowing seed to drop into the trench for proper contact with the soil. Notice the seeds embedded deep into the trench. Regardless of bare turf or established turf, using the Agrimetal W-24 over seeder guarantees you the best results every time.



- Features:
1. Tight  $\frac{3}{4}$  inch spacing from center to center
  2. Clean slitting on established turf, as well as, on bare turf
  3. Diamond pattern seeding without damaging the green.



Simply activate the metering drum and slitting rotor by lowering or raising one lever. The W-24 over seeder is powered by a reliable 9 HP Honda engine.

The W-24 does not require any tools for the depth adjustment.



Precise metering specially designed for bentgrass seed. Each hose has its own metering hole to assure even distribution. Seed flow control rate is directly related to ground speed for accurate seeding. The operator has a choice of 7 different flow rates to choose from.



For easy transportation from green to green a specially designed trailer is included with every W-24 overseeder.



## Specifications

Working width :	24" (60 cm)
Number of blades :	33
Blades center to center	$\frac{3}{4}$ " (1.90 cm)
Height:	43" (109 cm)
Width:	40" (102 cm)
Length :	56" (142 cm)
Engine :	9 HP HONDA
Machine weight :	370 Lbs (182 kg)
Shipping weight :	400 Lbs (168 kg)
Shipping dimensions:	38" x 46" x 36" (96.5 x 117 x 91cm)

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment & accessories, and may not illustrate all standard equipment.

See our overseeder in motion at [Agrimetal.com](http://Agrimetal.com). A reliable product offering high performance at low maintenance cost. A field demonstration will convince you. Call your nearest Agrimetal dealer for a demo on your course.

*patent pending*

# AgrMetal

[www.agrimetal.com](http://www.agrimetal.com)

Part number: NC13-72-0068

1006, rue Principale  
Wickham, Quebec  
Canada J0C 1S0  
tel.: 1-819-398-6883  
1-888-398-6883  
fax: 1-800-529-5311  
[service@agrimetal.com](mailto:service@agrimetal.com)

Your local dealer: