



CUSHMAN®



HAULER® 800

EFFICIENT AND RELIABLE, YOUR GO-TO VEHICLE.

The Cushman® Hauler® 800 is built to swiftly and easily move people and small equipment around any facility. Powered by your choice of a reliable 48-volt AC electric drivetrain or fuel-efficient 13.5 hp gas engine, the Hauler 800 is perfectly equipped to perform a variety of duties. With a spacious dash and a range of accessories tailored for superintendents, the Hauler 800 has a proven track record that can't be beat.

LET'S WORK.®

13.5HP
KAWASAKI
GAS

800LB
LOAD
CAPACITY

48V AC
ELECTRIC

900LB
TOW
CAPACITY



CUSHMAN® HAULER® 800



STANDARD BRUSH GUARD



RADIO CLIP



FUNCTIONAL DASH



MOISTURE METER RACK / BED DIVIDER

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Glove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- On-Board Charger (Elec. only)
- LED Headlights - Hi/Low
- Taillights
- Brakelights
- Hubcaps
- Ball Hitch Receiver
- Comfort Grip Steering Wheel
- High Altitude Jetting
- (Gas only)
- Fuel Gauge
- Battery Fill System (Elec. only)
- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Body Color (Patriot Blue, Forest Green, Ivory, Bright White, Flame Red, Orange, Black, Almond, Matte Black, Safety Yellow, Metallic Charcoal)
- Weather Enclosure
- Cab
- Ball Cage
- ROPS

	ELECTRIC	GAS
BODY & CHASSIS		
FRAME	Welded steel with E-Shield ecoat plus DuraShield™ powder coat	Welded steel with E-Shield ecoat plus DuraShield™ powder coat
BODY & FINISH	Injection Molded TPO (front), Injection Molded PP (rear)	Injection Molded TPO (front), Injection Molded PP (rear)
STANDARD COLOR	Forest Green	Forest Green
DIMENSIONS		
OVERALL LENGTH	110 in (280 cm)	110 in (280 cm)
OVERALL WIDTH	49 in (125 cm)	49 in (125 cm)
OVERALL HEIGHT	69.5 in (176 cm)	69.5 in (176 cm)
WHEEL BASE	65.5 in (166 cm)	65.5 in (166 cm)
FRONT WHEEL TRACK	37.0 in (94 cm)	37.0 in (94 cm)
REAR WHEEL TRACK	38.0 in (97 cm)	38.0 in (97 cm)
GROUND CLEARANCE	4.3 in (11 cm)	4.3 in (11 cm)
CARGO BOX CAPACITY	8.4 cu ft (0.24 m³)	8.4 cu ft (0.24 m³)
POWER		
POWERTRAIN	48-Volt AC Drive	4-cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	8.9 hp (6.6 kW) Peak	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	48-Volt	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPER)	Six 8-Volt Deep Cycle	One 12V Maintenance Free
KEY OR PEDAL START	Pedal	Pedal
OIL FILTER	n/a	Spin-On
COOLING SYSTEM	n/a	Air Cooled
FUEL CAPACITY	n/a	5.6 Gallon (21.3 L) Tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse	Forward-Reverse
REAR AXLE RATIO	16.99:1	11.47:1(Forward) 14.35:1(Reverse)
PERFORMANCE		
SEATING CAPACITY	2 Person	2 Person
CURB WEIGHT	1101 lb (499 kg)	791 lb (359 kg)
BED LOAD CAPACITY	400 lb (181 kg)	400 lb (181 kg)
VEHICLE LOAD CAPACITY	800 lb (360 kg)	800 lb (360 kg)
SPEED	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)
TOWING CAPACITY	900 lb (408kg) max	900 lb (408 kg) max
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	18.9 ft (5.8 m)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack and Pinion	
FRONT/REAR SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum	
PARKING BRAKE	Self-compensating, Single Point Engagement	
FRONT TIRES	K500 18 x 8.5 - 8 (6 ply rated)	
REAR TIRES	K500 18 x 8.5 - 8 (6 ply rated)	