



CUSHMAN®



HAULER® 1200

LOADED WITH RELENTLESS FUNCTIONALITY.

The new Hauler® 1200 is equipped to tackle the burden of every job, with a rugged truck-like design perfected by Superintendents. A large bed packed full of essential functionality can easily be converted for any task. Featuring tie down locations, divider slots and a full line of affordable accessories, transporting everything from sod to small equipment has never been easier. Your work is unforgiving, let the Hauler 1200 carry the load.

LET'S WORK.®

13.5HP
KAWASAKI
GAS

1500LB
TOW
CAPACITY

12 CU FT
CARGO
BED

1200LB
LOAD
CAPACITY



CUSHMAN® HAULER® 1200



LONG-HANDLED TOOL ATTACHMENT



SIDE FILL GAS TANK



IPAD/TABLET STORAGE



OPTIONAL ALUMINUM BED / POWER

OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Flexible Tool Clamps
- L-Track Aluminum Bed System
- Tie Down D-Loops
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Brushguard
- ROPS-Certified Ball Cage
- Weather Enclosure
- Rearview Mirror
- Color Options
- ROPS-Certified Cab
- Ladder/Hoop Rack

BODY & CHASSIS

FRAME	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO, Painted
STANDARD COLOR	Forest Green

DIMENSIONS

OVERALL LENGTH	115 in (292 cm)
OVERALL WIDTH	49.4 in (125 cm)
OVERALL HEIGHT W/ CANOPY	71 in (179 cm)
WHEEL BASE	76.8 in (195 cm)
FRONT WHEEL TRACK	35 in (89 cm)
REAR WHEEL TRACK	38.5 in (98 cm)
GROUND CLEARANCE	3.5 in (9 cm)
CARGO BOX CAPACITY	12 cu ft (0.34m ³)

POWER

POWER SOURCE	4-cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	Single Cylinder OHV
HORSEPOWER (KW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPE)	One 12V Maintenance Free
KEY OR PEDAL START	Pedal Start
AIR CLEANER	Dry Cartridge
LUBRICATION	Pressurized Oil System
OIL FILTER	Spin-On
COOLING SYSTEM	Air Cooled
FUEL CAPACITY	6 Gallon (22.7 L) Tank
DRIVE TRAIN	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears
GEAR SELECTION	Forward-Reverse
REAR AXLE RATIO	11.42:1(Forward) 15.78:1(Reverse)

PERFORMANCE

SEATING CAPACITY	2 Person
CURB WEIGHT	980 lb (445 kg)
BED LOAD CAPACITY	800 lb (364 kg)
VEHICLE LOAD CAPACITY	1200 lb (545 kg)
SPEED	14 mph ± 0.5 mph (24.1 kph ± 0.8 kph)
TOWING CAPACITY	1500 lb (680 kg) max
OUTSIDE CLEARANCE CIRCLE	23.0 ft (7 m)

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement
FRONT/REAR TIRES	18 x 8.5-8 (6 ply rated)