



CUSHMAN®



HAULER® 800X

MAKE TOUGH JOBS SIMPLE

The Cushman® Hauler® 800X features a lifted suspension that can navigate the most challenging areas of your course. With a customizable bed and practical accessories, it's designed with the versatility you need to build it your way. If topdressing, spot maintenance and debris management are critical to keeping your course in pristine condition, the Hauler 800X is ready to work.

LET'S WORK.®

13.5HP
KAWASAKI
GAS

725LB
LOAD
CAPACITY

48V AC
ELECTRIC

8.4 CU. FT
CARGO
BED



CUSHMAN® HAULER® 800X



CUSTOMIZABLE CARGO BED



FUNCTIONAL DASH



OPTIONAL HUBCAPS



OPTIONAL FLOOR MOUNT ATTACHMENT

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Glove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- On-Board Charger (Elec. only)
- LED Headlights - Hi/Low
- Taillights
- Brakelights
- Hubcaps
- Ball Hitch Receiver
- Comfort Grip Steering Wheel
- High Altitude Jetting
- (Gas only)
- Fuel Gauge
- Battery Fill System (Elec. only)
- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Body Color (Patriot Blue, Forest Green, Ivory, Bright White, Flame Red, Orange, Black, Almond, Matte Black, Safety Yellow, Metallic Charcoal)
- Weather Enclosure
- Cab
- Ball Cage
- ROPS

	ELECTRIC	GAS
BODY & CHASSIS		
FRAME	Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat	Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO (front), Injection Molded PP (rear)	Injection Molded TPO (front), Injection Molded PP (rear)
STANDARD COLOR	Forest Green	Forest Green
DIMENSIONS		
OVERALL LENGTH	110 in (280 cm)	110 in (280 cm)
OVERALL WIDTH	49 in (125 cm)	49 in (125 cm)
OVERALL HEIGHT (WITH CANOPY)	74 in (188 cm)	74 in (188 cm)
WHEEL BASE	65.5 in (166 cm)	65.5 in (166 cm)
FRONT WHEEL TRACK	37.0 in (94 cm)	37.0 in (94 cm)
REAR WHEEL TRACK	38.0 in (97 cm)	38.0 in (97 cm)
GROUND CLEARANCE	5.5 in (14 cm)	5.5 in (14 cm)
CARGO BOX CAPACITY	8.4 cu ft (0.24 m³)	8.4 cu ft (0.24 m³)
POWER		
POWERTRAIN	48 Volt AC Drive	4-cycle, 24.5 ci (401 cc) Cylinder
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	8.9 hp (6.6 kW) Peak	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	48 Volt	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPE)	Six, 8-Volt Deep Cycle	One 12-Volt Maintenance Free
KEY OR PEDAL START	Pedal	Pedal
OIL FILTER	n/a	Spin-On
COOLING SYSTEM	n/a	Air Cooled
FUEL CAPACITY	n/a	5.6 Gallon (21.3 L) Tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse	Forward-Reverse
REAR AXLE RATIO	16.99:1	11.47:1 (Forward) 14.35:1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	2 Person	2 Person
CURB WEIGHT	1122 lb (509 kg) - Standard Batteries	830 lb (376 kg)
BED LOAD CAPACITY	325 lb (147.4 kg)	325 lb (147.4 kg)
VEHICLE LOAD CAPACITY	725 lb (328 kg)	725 lb (328 kg)
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)
TOWING CAPACITY	500 lb (230 kg) max	500 lb (230 kg) max
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	18.9 ft (5.8 m)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack and Pinion	
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum	
PARKING BRAKE	Self-compensating, Single Point Engagement	
FRONT/REAR TIRES	K500 20 x 8.00 -10 (6 Ply Rated)	