



CUSHMAN



HAULER® PRO-X

GET MORE MILEAGE OUT OF EVERY WORK DAY.

Stand back and let the new Hauler® PRO-X raise your expectations on what a 72-volt AC powertrain can do. With its 50-mile range, silent operation and lifted suspension, the Hauler PRO-X will help you and your team work seamlessly without disrupting play. Outstanding energy efficiency, low operational costs and a dash that can accommodate everything from an iPad to a radio, the Hauler PRO-X is equipped for action. So throw a spreader in the bed, load up the crew and let's work!

LET'S WORK.®

72V
AC
ELECTRIC

1200LB
TOW
CAPACITY

12 CU FT
CARGO
BED

900LB
LOAD
CAPACITY



CUSHMAN® HAULER® PRO-X



LONG-HANDLED TOOL ATTACHMENT



STANDARD ON BOARD CHARGER



HIGHER GROUND CLEARANCE



OPTIONAL ALUMINUM BED/POWER DUMP

OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Flexible Tool Clamps
- L-Track Aluminum Bed System
- Tie Down D-Loops
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Brushguard
- ROPS-Certified Ball Cage
- Weather Enclosure
- Rearview Mirror
- Color Options
- ROPS-Certified Cab

BODY & CHASSIS

| | |
|----------------|---|
| FRAME | Welded Steel with DuraShield™ Powder Coat |
| BODY & FINISH | Injection Molded TPO, Painted |
| STANDARD COLOR | Forest Green |

DIMENSIONS

| | |
|--------------------------|---------------------|
| OVERALL LENGTH | 119 in (302.26 cm) |
| OVERALL WIDTH | 50 in (125.48 cm) |
| OVERALL HEIGHT W/ CANOPY | 77 in (196 cm) |
| WHEEL BASE | 78 in (197 cm) |
| FRONT WHEEL TRACK | 38.0 in (96.56 cm) |
| REAR WHEEL TRACK | 38.0 in (96.56 cm) |
| GROUND CLEARANCE | 7.2 in (18.29 cm) |
| CARGO BOX CAPACITY | 12 cu ft (0.340 m³) |

POWER

| | |
|---------------------|--|
| POWER SOURCE | 72-Volts |
| MOTOR TYPE | AC Induction |
| HORSEPOWER (KW) | 22.4HP (16.7 kW) - Measured at Peak Torque |
| ELECTRICAL SYSTEM | 72 Volt |
| BATTERY (QTY/TYPER) | Nine 8-Volt Deep Cycle |
| BATTERY CHARGER | 900 Watt 72V DC |
| KEY OR PEDAL START | Pedal |
| DRIVE TRAIN | Motor Shaft Direct Drive |
| TRANSAXLE | Differential with Helical Gears |
| SPEED CONTROLLER | 350 Amp AC |
| GEAR SELECTION | Forward-Neutral-Reverse |
| REAR AXLE RATIO | 17:1 |

PERFORMANCE

| | |
|--------------------------|---|
| SEATING CAPACITY | 2 Person |
| CURB WEIGHT | 1513 lb (686 kg) |
| BED LOAD CAPACITY | 500 lb (227 kg) |
| VEHICLE LOAD CAPACITY | 900 lb (408 kg) |
| SPEED | 16.5 mph +/- 0.5 mph (26.6 kph +/- 0.8 kph) |
| TOWING CAPACITY | 1200 lb (544 kg) max |
| OUTSIDE CLEARANCE CIRCLE | 24.0 ft (7.3 m) |

STEERING & SUSPENSION

| | |
|-----------------------|--|
| STEERING | Self-Compensating Rack and Pinion |
| FRONT/REAR SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers |
| SERVICE BRAKE | Rear Wheel Mechanical Self-adjusting Drum |
| PARKING BRAKE | Self-compensating, Single Point Engagement |
| FRONT/REAR TIRES | 20 x 8.10 (6 Ply Rated) |