

MODEL	73-000 Sweep Star V72E (Big Vac 72-E)		
POWER	31 hp (23 kW) Twin Cylinder, OHV, air cooled gasoline engine with Donaldson air intake filtration, full pressure lubrication system		
CONFIGURATION	72 Inch (183 cm) Sweeping Width, Self Contained, two wheel, pull type sweeper and vacuum for turf and other surfaces. Pulls behind appropriate tow vehicles.		
DEBRIS HOPPER			
	CAPACITY:	7 cubic yards (5.1 cubic meters)	
	CONSTRUCTION:	14 gauge steel formed panels Tapered front to back for easy dumping Air exhaust vents built into top of debris hopper	
	DUMP:	Hydraulic raise/lower of debris hopper and	
SWEEPER HEAD OPTIONS (Requires one below)			

SWEEPER HEAD, 72 in (183 cm) Sweeping Width to dislodge debris from ground surface. Hydraulic motor drive from base unit hydraulic system

One Sweeper Head must be selected: 72-005 Nylon Brush sweeper head 72-002 Rubber finger sweeper head

## TOW HITCH OPTIONS (Requires one below)

**73-004** 5<sup>th</sup> wheel hitch for use with Textron vehicles equipped with 5<sup>th</sup> wheel hitch device and trailer brake option

**73-005** 5<sup>th</sup> wheel hitch for use with tractor 3 point hitch (Min 35 hp [27 kW] tractor)

73-003 Clevis hitch for use behind tractors, trucks

VACUUM SYSTEM 22 in (57 cm) diameter x 7 in. (18 cm) wide, 1/4" (.7cm), balanced, high strength Abrasion resistant impeller, 3800 CFM displacement, operating inside high strength steel housing With wear resistant, replaceable liner, large clean out door and drain plug.

> Connected to sweeper head with flexible air tunnel to remove debris from ground surface and deposit into debris hopper

DRIVE Engine drives hydraulic pump to power sweeper head hydraulic motor Belt drives vacuum impeller through electric clutch

	Electric brakes optional, require the use of 73-004 5 <sup>th</sup> wheel hitch connected to Jacobsen Turf Truckster, which is equipped with 5 <sup>th</sup> wheel hitch option and electric trailer brake option.
CONSTRUCTION	Hydraulically formed, electrically welded heavy wall rectangular and steel tubing
AXLE	High strength axle tube, 3500 lb. (1590 kg) rated axle
TIRES/WHEELS	(2) 26.5-1400 x 12 Fairway type Turf type
INSTRUMENTATION	Hydraulic open close of debris hopper tailgate Hydraulic raise / lower of sweeping mechanism head assembly Electric (toggle switch) engage of vacuum impeller electric clutch Increase/decrease engine speed Remote engine start
SOUND LEVEL	98 dbA
<b>DIMENSIONS(Inches/cm)</b> (Length-Width-Height)	180 in (458 cm) – 84 in (214 cm) – 87 in (221 cm)
WEIGHT	2950 lbs (1338 kg <b>)</b>
LIQUID CAPACITIES	Gasoline (unleaded): 5 gallons (19 liter) in high density nylon low-perm tank Hydraulic system oil: 3.2 gallons (12.2 liter) in high density polyethylene tank
SAFETY & CONFORMANCE	Complies with all applicable ANSI, OSHA, and European Machinery Directive

## **OPTIONS & ACCESSORIES**

**73-006** 25 ft. (7.6m) Hand held vacuum hose